

## DIMMER COMPATIBILITY CLASSIC P

### BASIC INFORMATION:

#### 1. WHAT IS THE PRODUCT CODE AND WHERE DO I FIND IT?

The product code describes the lamp type. It contains 7 letters and digits and is starting with "A". Below an example for the product code of the stamp of the lamp:



#### 2. HOW CAN I READ THE FOLLOWING CHARTS?

Legend:  
Information about the dimmability of the lamps. Green means very good dimmability, yellow means limited dimmability, red means undesired dimmability etc.

List of dimmers tested in laboratory conditions

Legend					SUPERSTAR PAR16 35 36°				SUPERSTAR PAR16 50 36°				SUPERSTAR PAR16 80 36°				SUPERSTAR PAR16 80 120°															
Very good dimmability with indicated number of lamps (dimming range greater than 75%)																																
Limited dimmability with indicated number of lamps (dimming range smaller than 75%)																																
Undesired dimmability																																
Not relevant																																
Not tested																																
EAN/Basic Code					4052839330153/AC01184				4052839330157/AC01152				4052839330174/AC01167				4052839330195/AC01134				4052839330232/AB41306				4058075036589/AC03043				4058075036582/AC03051			
Dimmer					Number of Lamps		Dimming range		Number of Lamps		Dimming range		Number of Lamps		Dimming range		Number of Lamps		Dimming range													
ABB	STD 50-3	230/50Hz	60-500	L	1-20	98% - 15%	1-13	98% - 20%	1-8	97% - 23%	1-8	97% - 23%	1-20	98% - 15%	2-20	97% - 12%	2-20	98% - 16%	2-20	98% - 16%												
Altenburger Electronic	50 30	230/50Hz	15-350	T	1-10	98% - 15%	2-10	97% - 12%	1-4	96% - 1%	1-4	96% - 1%	1-20	98% - 15%	2-20	97% - 12%	2-20	98% - 16%	2-20	98% - 16%												
ALPORA	DSP 400	230/50Hz	400	L	1-10	98% - 15%	2-10	97% - 12%	1-4	96% - 1%	1-4	96% - 1%	1-20	98% - 15%	2-20	97% - 12%	2-20	98% - 16%	2-20	98% - 16%												
Berker	2861	230/50Hz	50-420	U	1-20	98% - 27%	1-20	98% - 26%	1-20	97% - 27%	1-20	97% - 27%	1-15	98% - 1%	1-10	97% - 5%	1-6	94% - 7%	1-6	94% - 7%												
Blicino	LNNT441N	230/50Hz			2-20	98% - 1%	2-9	98% - 1%	1-6	97% - 9%	1-6	97% - 9%	3-19	99% - 19%	2-12	97% - 19%	1-8	95% - 22%	1-8	95% - 22%												
Blicino	LNNT4408	230/50Hz	40-420	T	2-20	99% - 15%	2-20	98% - 17%	2-20	98% - 21%	2-20	98% - 21%	2-20	99% - 15%	2-20	98% - 17%	2-20	98% - 21%	2-20	98% - 21%												
Blicino	NT4402N	230/50Hz	500	R	1-10	96% - 22%	1-10	97% - 26%	1-10	97% - 15%	1-9	97% - 15%	1-10	96% - 22%	1-10	97% - 26%	1-10	97% - 15%	1-9	97% - 15%												
Busch-Jaeger	6513 U-102	230/50Hz	40-420	T	1-10	98% - 34%	1-10	97% - 35%	1-5	97% - 15%	1-5	97% - 15%	1-20	98% - 15%	1-13	98% - 20%	1-8	97% - 23%	1-8	97% - 23%												
Busch-Jaeger	6523 U-102	230/50Hz	420	T	2-13	98% - 1%	1-10	98% - 5%	1-6	97% - 9%	1-6	97% - 9%	2-20	98% - 1%	1-10	98% - 5%	1-6	97% - 9%	1-6	97% - 9%												
Busch-Jaeger	2250 U	230/50Hz	60-600	L	1-11	98% - 1%	1-10	99% - 1%	1-5	99% - 7%	1-5	99% - 7%	1-10	98% - 1%	1-10	99% - 1%	1-5	99% - 7%	1-5	99% - 7%												
Busch-Jaeger	6526 U	230/50Hz			1-10	98% - 1%	1-10	97% - 4%	1-4	97% - 1%	1-4	97% - 1%	1-10	98% - 1%	1-10	98% - 7%	1-20	97% - 10%	1-20	97% - 10%												
Busch-Jaeger	2247 U-500	230/50Hz	60-600	L	1-20	98% - 1%	1-13	97% - 1%	1-8	96% - 1%	1-8	96% - 1%	1-20	98% - 1%	1-13	97% - 1%	1-8	96% - 1%	1-8	96% - 1%												
CENTURY CONTROL	MULTI DIMMER	230/50Hz	60-600	L	1-14	98% - 1%	1-13	97% - 4%	1-10	97% - 19%	1-10	97% - 19%	1-10	98% - 1%	1-13	97% - 4%	1-10	97% - 19%	1-10	97% - 19%												
DINUY	RE EL1LE1	230/50Hz	400	LED																												
ELKO	400GLI	230/50Hz																														
ELKO	315GLE	230/50Hz	20-315	T																												
ELKO	600GLI	230/50Hz	40-600	U																												
ELKO	420GLEI	230/50Hz	40-420	U																												

Information about the OSRAM lamp type

Assessment of the results into categories. Includes the number of lamps and the related dimming range

## DIMMER KOMPATIBILITÄT CLASSIC P

### BASISINFORMATIONEN:

#### 1. WAS IST DER PRODUKTCODE UND WO FINDE ICH IHN?

Der Produktcode beschreibt den Lampentyp. Er besteht aus sieben Buchstaben und Ziffern und beginnt mit einem "A". Nachfolgend ein Beispiel eines Produktcodes auf dem Aufdruck der Lampe.



220-240V **AC01770** 2700K  
13 W 50/60 Hz 27 mA  
Made in Germany XXX-XXXX

#### 2. WIE LESE ICH DIE FOLGENDEN TABELLEN?

Legende: Angaben zur Dimmbarkeit der Lampen. Grün bedeutet eine sehr gute Dimmbarkeit mit der angegebenen Lampenanzahl, gelb bedeutet eine eingeschränkte Dimmbarkeit, rot bedeutet, dass unerwünschtes dimmverhalten auftreten kann etc.












Liste der getesteten Dimmer

Legend					SUPERSTAR							
Very good dimmability with indicated number of lamps (dimming range greater than 75%)					PAR16 35 36*	PAR16 50 36*	PAR16 60 36*	PAR16 60 120*				
Limited dimmability with indicated number of lamps (dimming range smaller than 75%)												
Undesired dimmability					EAN/ Basic Code	EAN/ Basic Code	EAN/ Basic Code	EAN/ Basic Code				
Not relevant					405283330133/AC01184	405283330171/AC01187	405283330210/AB41305	405807503668/AC03049				
Not tested					405283330157/AC01192	405283330199/AC01194	405283330232/AB41306	405807503632/AC03051				
Dimmer					Number of Lamps	Dimming range	Number of Lamps	Dimming range	Number of Lamps	Dimming range	Number of Lamps	Dimming range
ABB	STD 50-3	230V50Hz	60-500	L	1-20	98%-15%	1-13	98%-20%	1-8	97%-23%	1-8	97%-23%
Altenburger Electronic	50 30	230V50Hz	15-350	T	2-20	98%-15%	2-20	97%-12%	2-20	98%-16%	2-20	98%-16%
AURORA	DSP 400	230V50Hz	400	L	1-10	98%-15%	2-10	97%-14%	1-4	96%-1%	1-4	96%-1%
Berker	2861	230V50Hz	50-420	U	1-20	98%-27%	1-20	98%-25%	1-20	97%-27%	1-20	97%-27%
Bicimo	LJNNT441N	230V50Hz			1-15	98%-1%	1-10	97%-5%	1-6	94%-7%	1-6	94%-7%
Bicimo	LJNNT4408	230V50Hz			2-20	98%-1%	2-9	98%-1%	1-6	97%-3%	1-6	97%-3%
Bicimo	NT4402N	230V50Hz	500	R	3-18	99%-19%	2-12	97%-19%	1-8	95%-22%	1-8	95%-22%
Busch-Jaeger	6513 U-102	230V50Hz	40-420	T	2-20	98%-15%	2-20	98%-17%	2-20	98%-21%	2-20	98%-21%
Busch-Jaeger	6523 U-102	230V50Hz	420	T	1-10	96%-22%	1-10	97%-26%				
Busch-Jaeger	2250 U	230V50Hz	60-600	L	1-10		2-14	98%-16%	1-9	97%-15%	1-9	97%-15%
Busch-Jaeger	6526 U	230V50Hz			1-13	98%-34%	1-10	97%-35%	1-5		1-5	
Busch-Jaeger	2247 U-500	230V50Hz			1-20	98%-15%	1-13	98%-20%	1-8	97%-23%	1-8	97%-23%
CENTURY CONTROL	MULTI DIMMER	230V50Hz	60-600	L	2-13	98%-1%	1-10	98%-5%	1-6	97%-9%	1-6	97%-9%
DINJY	RE EL1LE1	230V50Hz	400	LED	1-11	98%-1%	1-10	98%-1%	1-5	99%-7%	1-5	99%-7%
ELKO	400GLI	230V50Hz			1-10		1-10		1-4	97%-1%	1-4	97%-1%
ELKO	316GLE	230V50Hz	20-315	T	2-20	98%-6%	1-20	98%-7%	1-20	97%-10%	1-20	97%-10%
ELKO	600GLI	230V50Hz	40-600	U	1-20	98%-1%	1-13	97%-1%	1-8	96%-1%	1-8	96%-1%
ELKO	420GLEI	230V50Hz	40-420	U	1-14	98%-1%	1-13	97%-4%	1-10	97%-19%	1-10	97%-19%












Angaben zum OSRAM Lampentyp

Bewertung der Testergebnisse in Ampel Kategorien. Beinhaltet sowohl die Lampenanzahl als auch den dimmbaren Bereich












## DIMMER COMPATIBILITY CLASSIC P

Legend					SUPERSTAR CL P 25 FIL/GL FR E27	SUPERSTAR CL P 25 FIL/GL FR E14	SUPERSTAR CL P 35 FIL Mirror Silver	SUPERSTAR CL P 40 Frosted	SUPERSTAR CL P 40 FIL/GL FR E27	SUPERSTAR CL P 40 FIL/GL FR E14	SUPERSTAR CL P 40 FIL/GL FR E14					
	Very good dimmability with indicated number of lamps (dimming range greater than 75%)															
	Limited dimmability with indicated number of lamps (dimming range smaller than 75%)				EAN / Basic Code	EAN / Basic Code	EAN / Basic Code	EAN / Basic Code	EAN / Basic Code	EAN / Basic Code	EAN / Basic Code					
	Undesired dimmability															
	Not relevant															
Not tested					4058075108189 / AC16952 4058075211407 / AC16952 4058075808775 / AC16979 4058075054301 / AC16936	4058075108141 / AC16951 4058075211384 / AC16951 4058075808751 / AC16935 4058075054288 / AC16935	4058075132931 / AC17530	4052899900905 / AC17466	405807511790 / AC16959 4058075814875 / AC16986 4058075211063 / AC16986 4058075234079 / AC16986 4058075808799 / AC16980 4058075808805 / AC16981 4058075054349 / AC16938 4058075233898 / AC16980	4052899961845 / AC16929 405807511776 / AC16958 4058075211049 / AC16929 4052899959293 / AC16927 4058075054325 / AC16937 40580752132795 / AC16973	4058075808911 / AC16983 4058075108448 / AC16957 4058075132214 / AC16971 4058075234055 / AC16957 4058075233836 / AC16983					
Dimmer					Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps
ABB	STD 50-3	230/50Hz	60-500	L	84-0%	84-0%	87-0%	87-0%	78-0%	96-0%	95-6%	95-6%	85-3%	90-0%	90-0%	99-0%
Altenburger	50,3	230/50Hz				86-0%		89-0%	84-0%		96-0%		50-0%			100-0%
AURORA	DSP 400	230/50Hz	400	L						85-0%						94-0%
Berker	2861	230/50Hz	50-420	U	81-7%	87-4%	83-7%	90-4%	93-0%	92-0%			93-2%	92-2%	100-0%	98-0%
Bticino	L/N/NT4411N	230/50Hz			100-0%	100-0%	100-0%	100-0%	91-0%	91-0%	91-0%	100-0%	97-0%	97-0%	100-0%	86-0%
Bticino	L/N/NT4408	230/50Hz							93-0%	95-0%	95-0%	96-0%		93-0%		92-0%
bticino	NT4402N	230/50Hz	500	R							96-0%					96-0%
Busch-Jaeger	6513 U-102	230/50Hz	420	T	100-27%	100-3%	100-28%	100-1%	94-0%	94-0%		100-0%	100-22%	100-0%		100-0%
Busch-Jaeger	6523 U-102	230/50Hz	40-420	T		100-3%		100-1%	94-1%	94-1%	98-0%	100-0%		100-0%		100-0%
Busch-Jaeger	2250 U	230/50Hz	60-600	L							96-0%					
Busch-Jaeger	6526 U	230/50Hz			84-5%	86-3%	87-5%	88-3%	95-3%	95-8%	90-12%		90-5%	91-12%	89-5%	91-12%
CENTURY CONTROL	MULTI DIMMER	230/50Hz	60-600	U	78-1%	84-0%	80-1%	87-0%	87-0%	94-0%	97-0%	96-0%	90-0%	92-0%	89-0%	91-0%
DimMax	420 SL	230/50Hz	200	L/T	100-0%	100-0%	100-0%	100-0%	94-0%	96-0%			100-0%	97-0%	100-0%	100-0%
DINUY	RE EL1 LE1	230/50Hz	400	LED	86-0%	87-0%	88-0%	89-0%	93-1%	93-1%	96-0%	97-0%	96-0%	96-0%	95-0%	98-0%
ELKO	400GLI	230/50Hz				100-0%			53-0%	88-0%	95-0%	99-0%		91-0%	100-0%	88-0%
ELKO	315GLE	230/50Hz	20-315	T		100-0%		100-0%	72-0%	93-0%	100-0%	100-0%		100-0%	100-0%	98-0%
ELKO	600GLE/I	230/50Hz			87-0%	100-0%		100-0%	89-0%	93-0%	57-0%		90-0%	96-0%		97-0%
ELKO	600GLi	230/50Hz	40-600	U	78-0%	87-0%	80-0%	89-0%	94-0%	96-0%	93-0%	95-0%	75-0%	91-0%	74-0%	93-0%
ELKO	420GLE/I	230/50Hz	40-420	U		87-0%		89-0%		96-0%	85-0%	97-0%		92-0%	91-0%	86-0%
ELKO	1000LRI	230/50Hz			84-0%	84-0%	87-0%	87-0%	93-0%	96-0%	96-0%		90-0%	91-0%	90-0%	91-0%
ELKO	630GLE	230/50Hz	20-630	U	74-6%	100-1%		100-0%	48-3%	52-4%	96-0%	96-0%		97-0%	100-0%	99-0%
Eltako	EUD61NPN-UC	230/50Hz	5-400	R/L/C	87-0%	87-0%	89-0%	89-0%			96-0%	97-0%	96-0%	96-0%	95-0%	95-0%
Feller	40200.LEDxxx	230/50Hz				87-0%		90-0%	94-0%	95-0%	96-0%	96-0%		94-0%	91-0%	93-0%
Feller	40600.RLC	230/50Hz	20-600	U	87-0%	100-0%		100-0%	89-0%	93-0%	57-0%		90-0%	96-0%		97-0%
Feller	40600.RC	230/50Hz			74-6%	100-1%		100-0%	48-3%	52-4%	96-0%	96-0%		97-0%		100-0%
Feller	40600.RL	230/50Hz			78-0%	87-0%	80-0%	89-0%	94-0%	96-0%	93-0%	95-0%	75-0%	91-0%	74-0%	91-0%
Feller	40420.RLC	230/50Hz				87-0%		89-0%		96-0%	85-0%	97-0%		92-0%	91-0%	86-0%
Feller	31000	230/50Hz			84-0%	84-0%	87-0%	87-0%	93-0%	96-0%	96-0%		90-0%	91-0%	90-0%	91-0%
GIRA	226200	230/50Hz				100-0%		100-0%	70-1%	95-0%	96-0%	100-0%	89-2%	100-0%		87-0%
Gira	030700	230/50Hz	20-525	T	100-8%	100-0%	100-7%	100-0%	96-1%	94-0%	100-0%	100-0%	100-4%	100-0%	100-5%	100-0%
Gira	117600	230/50Hz	50-420	U		87-5%		89-5%	92-5%	93-10%				93-3%		92-3%
Gira	238500	230/50Hz						95-2%	95-0%					93-0%		92-0%

## DIMMER COMPATIBILITY CLASSIC P

Legend					SUPERSTAR CL P 25 FIL/GL FR E27	SUPERSTAR CL P 25 FIL/GL FR E14	SUPERSTAR CL P 35 FIL Mirror Silver	SUPERSTAR CL P 40 Frosted	SUPERSTAR CL P 40 FIL/GL FR E27	SUPERSTAR CL P 40 FIL/GL FR E14	SUPERSTAR CL P 40 FIL/GL FR E14						
	Very good dimmability with indicated number of lamps (dimming range greater than 75%)																
	Limited dimmability with indicated number of lamps (dimming range smaller than 75%)				EAN / Basic Code	EAN / Basic Code	EAN / Basic Code	EAN / Basic Code	EAN / Basic Code	EAN / Basic Code	EAN / Basic Code						
	Undesired dimmability																
	Not relevant																
Not tested					4058075108189 / AC16952 4058075211407 / AC16952 4058075808775 / AC16979 4058075054301 / AC16936	4058075108141 / AC16951 4058075211384 / AC16951 4058075808751 / AC16935 4058075054288 / AC16935	4058075132931 / AC17530	4052899900905 / AC17466	405807511790 / AC16959 4058075814875 / AC16986 4058075211063 / AC16986 4058075234079 / AC16986 4058075808799 / AC16980 4058075808805 / AC16981 4058075054349 / AC16938 4058075233898 / AC16980	4052899961845 / AC16929 405807511776 / AC16958 4058075211049 / AC16929 4052899959293 / AC16927 4058075054325 / AC16937 4058075132795 / AC16973	4058075808911 / AC16983 4058075108448 / AC16957 4058075132214 / AC16971 4058075234055 / AC16957 4058075233836 / AC16983						
Dimmer					Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps	
Brand	Model	Voltage range	Power	Type													
Gira	217400	230/50Hz	4X20-250	KNX-U	87-0%	87-0%	89-0%	89-0%	98-3%	92-0%	96-0%	96-0%	91-0%	94-0%	97-0%	96-0%	
Hager	WUD87	230/50Hz	400	LED-U	84-0%	84-0%	87-0%	87-0%	86-0%	94-0%	96-0%	96-0%	90-0%	91-0%	90-0%	100-0%	
Hamilton	KP1X40	230/50Hz	400										72-0%	72-0%			
Hugo Müller	paladin 872110 led	230/50Hz			86-0%	87-0%	88-0%	89-0%	93-1%	93-1%	96-0%	97-0%	96-0%	95-0%	95-0%	98-0%	98-0%
Jung	225 NVDE	230/50Hz	20-500	L		100-0%		100-0%	70-1%	95-0%	96-0%	100-0%	89-2%	100-0%		87-0%	98-0%
Jung	225 TDE	230/50Hz			100-8%	100-0%	100-7%	100-0%	96-1%	94-0%	100-0%	100-0%	100-4%	100-0%	100-5%	100-0%	100-0%
Jung	254 UDIE1	230/50Hz				87-5%		89-5%	92-5%	93-10%				93-3%		92-3%	
Jung	1224 LEDUDE	230/50Hz		LED					95-2%	95-0%				93-0%		92-0%	99-0%
Jung	3904 REGHE	230/50Hz				87-0%		89-0%	98-3%	92-0%	96-0%	96-0%	91-0%	94-0%	91-0%	93-0%	97-0%
Legrand	665114	230/50Hz	400	U	100-0%	100-0%	100-0%	100-0%	91-0%	91-0%	91-0%	100-0%	97-0%	97-0%	100-0%		86-0%
Legrand	067083=048869=048869=0	230/50Hz			100-0%	100-0%	100-0%	100-0%	91-0%	91-0%	91-0%	100-0%	97-0%	97-0%	100-0%		86-0%
Legrand	770061	230/50Hz	400	RL					94-0%	93-0%	96-0%	96-0%					96-0%
Legrand	099314	230/50Hz	300	RL	69-17%	86-0%		88-0%	93-0%	94-0%	95-0%	95-0%					95-0%
Legrand	770062	230/50Hz	400	RLC		84-0%		87-0%		94-0%	95-0%	96-0%					98-0%
Legrand	078405	230/50Hz	600	RL					93-0%	95-0%	95-0%	96-0%		93-0%		92-0%	96-0%
MASTER	DM-DGL	230/50Hz	1000	U / LED	82-1%	82-0%	84-1%	84-0%	87-28%	94-29%			87-0%	96-0%	86-0%	95-0%	97-0%
MASTER	DM-2500	230/50Hz	2500	U / LED	82-0%	84-0%	84-0%	87-0%	91-0%	94-0%	96-0%	96-0%	90-0%	96-0%	89-0%	95-0%	96-0%
Merten	MEG5136-0000	230/50Hz				100-0%		100-0%	72-0%	93-0%	100-0%	100-0%		100-0%		100-0%	100-0%
Merten	MEG5134-0000	230/50Hz				87-0%		90-0%	94-0%	95-0%	96-0%	96-0%		94-0%	91-0%	93-0%	100-0%
Merten	MEG5139-0000	230/50Hz			87-0%	100-0%		100-0%	89-0%	93-0%	57-0%		90-0%	96-0%		97-0%	
Merten	MEG5137-0000	230/50Hz			74-6%	100-1%		100-0%	48-3%	52-4%	96-0%	96-0%		97-0%		100-0%	99-0%
Merten	MEG5133-0000	230/50Hz			78-0%	87-0%	80-0%	89-0%	94-0%	96-0%	93-0%	95-0%	75-0%	91-0%	74-0%	91-0%	93-0%
Merten	MEG5138-0000	230/50Hz				87-0%		89-0%		96-0%	85-0%	97-0%		92-0%		91-0%	86-0%
Merten	MEG 5170-0300	230/50Hz	10-200	U		86-0%		88-0%	93-1%	91-0%	96-0%		92-0%		91-0%	99-0%	100-0%
Merten	MEG 5131	230/50Hz	40-400	L	79-0%	87-0%	81-0%	89-0%	93-0%	96-0%	93-0%	94-0%	72-0%	91-0%	72-0%	91-0%	92-0%
Merten	MEG 5132	230/50Hz			79-0%	87-0%	81-0%	89-0%	93-0%	96-0%	93-0%	94-0%	72-0%	91-0%	72-0%	91-0%	92-0%
Merten	MEG 5140	230/50Hz	9-100	L		88-0%		90-0%	62-0%	96-0%	93-0%	95-0%		92-0%		91-0%	92-0%

## DIMMER COMPATIBILITY CLASSIC P

Legend					SUPERSTAR CL P 25 FIL/GL FR E27	SUPERSTAR CL P 25 FIL/GL FR E14	SUPERSTAR CL P 35 FIL Mirror Silver	SUPERSTAR CL P 40 Frosted	SUPERSTAR CL P 40 FIL/GL FR E27	SUPERSTAR CL P 40 FIL/GL FR E14	SUPERSTAR CL P 40 FIL/GL FR E14					
	Very good dimmability with indicated number of lamps (dimming range greater than 75%)															
	Limited dimmability with indicated number of lamps (dimming range smaller than 75%)															
	Undesired dimmability															
	Not relevant															
Not tested					4058075108189 / AC16952 4058075211407 / AC16952 4058075808775 / AC16979 4058075054301 / AC16936	4058075108141 / AC16951 4058075211384 / AC16951 4058075808751 / AC16935 4058075054288 / AC16935	4058075132931 / AC17530	4052899900905 / AC17466	405807511790 / AC16959 4058075814875 / AC16986 4058075211063 / AC16986 4058075234079 / AC16986 4058075808799 / AC16980 4058075808805 / AC16981 4058075054349 / AC16938 4058075233898 / AC16980	4052899961845 / AC16929 405807511776 / AC16958 4058075211049 / AC16929 4052899959293 / AC16927 4058075054325 / AC16937 4058075132795 / AC16973	4058075808911 / AC16983 4058075108448 / AC16957 4058075132214 / AC16971 4058075234055 / AC16957 4058075233836 / AC16983					
Brand	Model	Voltage range	Power	Type	Dimming	Dimming	Dimming	Dimming	Dimming	Dimming	Dimming	Dimming	Dimming	Dimming	Dimming	Dimming
					range 1 Lamp	range 4 Lamps	range 1 Lamp	range 4 Lamps	range 1 Lamp	range 4 Lamps	range 1 Lamp	range 4 Lamps	range 1 Lamp	range 4 Lamps	range 1 Lamp	range 4 Lamps
Merten	MEG 5135	230/50Hz	60-1000	L	84-0%	84-0%	87-0%	87-0%	93-0%	96-0%	96-0%	90-0%	91-0%	69-0%	99-0%	99-0%
MK	K4501	230/50Hz	180	L	84-0%	84-0%	87-0%	87-0%	58-0%	91-0%	96-0%	96-0%	70-0%	69-0%	99-0%	99-0%
NEXUS	881P-01	230/50Hz	400	L	84-0%	84-0%	87-0%	87-0%	50-0%	95-0%	96-0%	95-0%	93-0%	92-0%	94-0%	99-0%
NIKO	310-01900	230/50Hz	5-200	U	88-0%	88-0%	91-0%	91-0%	95-0%	97-0%	96-0%	96-0%	96-0%	95-0%	96-0%	98-0%
NIKO	330-00700	230/50Hz	5-200	U	88-0%	88-0%	91-0%	91-0%	96-0%	95-0%	96-0%	96-0%	96-0%	95-0%	95-0%	97-0%
Odace	S520512	230/50Hz				87-0%	90-0%	94-0%	95-0%	96-0%	96-0%		94-0%	91-0%	93-0%	100-0%
Odace	S520511	230/50Hz			78-0%	87-0%	80-0%	89-0%	94-0%	96-0%	93-0%	95-0%	75-0%	91-0%	74-0%	93-0%
Odace	S520515	230/50Hz				87-0%	89-0%	96-0%	85-0%	97-0%			92-0%	91-0%	86-0%	95-0%
Odace	S520518	230/50Hz				88-0%	90-0%	62-0%	96-0%	93-0%	95-0%		92-0%	91-0%	92-0%	99-0%
Osram	HTi DALI 315 DIM	230/50Hz	20-315	DALI-T	100-0%	100-0%	100-0%	100-0%		100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%
PEHA	435 HAN	230/50Hz	60-600	L		81-0%	83-0%		87-0%	93-0%	93-0%			91-0%	88-0%	98-0%
Schneider	400GLI	230/50Hz	40-400	T		100-0%		53-0%	88-0%	95-0%	99-0%		91-0%	100-0%	88-0%	99-0%
Schneider	SBD315SRC	230/50Hz				100-0%	100-0%	72-0%	93-0%	100-0%	100-0%		100-0%	100-0%	98-0%	100-0%
Schneider	SBD200LED	230/50Hz	400			87-0%	90-0%	94-0%	95-0%	96-0%	96-0%		94-0%	91-0%	93-0%	100-0%
Schneider	SBD600RCRL	230/50Hz			87-0%	100-0%	100-0%	89-0%	93-0%	57-0%		90-0%	96-0%	97-0%		100-0%
Schneider	SBD630RC	230/50Hz			74-6%	100-1%	100-0%	48-3%	52-4%	96-0%	96-0%		97-0%	100-0%	99-0%	100-0%
Schneider	SBD600RL	230/50Hz			78-0%	87-0%	80-0%	89-0%	94-0%	96-0%	93-0%	95-0%	75-0%	91-0%	74-0%	91-0%
Schneider	SBD420RCRL	230/50Hz				87-0%	89-0%		96-0%	85-0%	97-0%		92-0%		91-0%	86-0%
Schneider	5170	230/50Hz				86-0%	88-0%	93-1%	91-0%	96-0%			92-0%	91-0%	99-0%	100-0%
Schneider	SBD400RL	230/50Hz			79-0%	87-0%	81-0%	89-0%	93-0%	96-0%	93-0%	94-0%	72-0%	91-0%	72-0%	91-0%
Schneider	SBDSP	230/50Hz				88-0%	90-0%	62-0%	96-0%	93-0%	95-0%		92-0%		91-0%	92-0%
Schneider	ATTD1000RL	230/50Hz			84-0%	84-0%	87-0%	87-0%	93-0%	96-0%	96-0%		90-0%	91-0%	90-0%	91-0%
Shuttle	SDIM-T-LED-500W	230/50Hz	2-500	T & LED-T	84-0%	83-0%	87-0%	85-0%	91-0%	96-1%	96-0%	96-0%	87-0%	92-0%	86-0%	91-0%
Siemens	5TC8 284	230/50Hz	20-525	T		97-0%		69-4%	95-0%		100-0%				96-0%	100-0%
Siemens	5WG1-528-1AB31	230/50Hz	20-500	KNX-U		88-0%	91-0%		96-0%	96-0%	96-0%	96-0%	95-0%	95-0%	97-0%	97-0%
VADSBO	LD 220	230/50Hz	1-200	U	84-0%	83-0%	87-0%	85-0%	94-23%	95-22%	96-0%	93-0%	92-31%	92-23%	91-31%	91-22%
VARILIGHT	HQ3W	230/50Hz	400			74-0%	76-0%	82-0%	93-0%	96-0%	66-0%		90-0%		89-0%	100-0%
VARILIGHT	JQP401W	230/50Hz	400	T				76-0%		95-0%						97-0%
Vimar	20135	230/50Hz	3-100	U	87-0%	87-0%	89-0%	89-0%	96-0%	97-0%	96-0%	96-0%	96-0%	95-0%	95-0%	96-0%
ZANO	WH401	230/50Hz	400	L		83-0%	85-0%	77-0%	93-0%		95-0%		91-0%	92-0%	91-0%	92-0%
ZANO	WH251	230/50Hz	250								95-0%					99-0%
ZANO	Z GRID 700	230/50Hz	250	LED	84-0%	83-0%	87-0%	85-0%	91-0%	94-0%		93-0%	93-0%	92-0%	92-0%	100-0%
ZANO	Z GRID 500	230/50Hz	500			83-0%	85-0%	95-0%	95-0%		96-0%	83-0%	94-0%	82-0%	93-0%	93-0%

**Please Note:**

- The compatibility list is based upon testing conducted by the manufacturer in a lab simulated environment, and the results can vary in certain field applications due to a number of factors. OSRAM does not take over any responsibility, warranty or liability that this results can also achieved by using the devices under other conditions, or when using successor models of the tested devices, or different models of the same manufacturer, or when using other LED lamp types
- The absence of a dimmer from this chart does not necessarily imply incompatibility.
- Please reference the dimmer manufacturer's instructions for installation.
- LED lamps contain several electronic components. Under unfavourable conditions these can lead to acoustic noise. In case of resonance even low noise can cause audible effect. Possible factors influencing this are the installation, the design of the lamp holder and the luminaire (acoustic resonance effect) as well as the dimmer or the transformer (harmonics or electronic resonance).
- Subject to change without notice
- Errors and omission excepted
- Always make sure to use the most recent release

**Application Notes:**

- For best dimming results trailing edge dimmer type is recommended.
- Trailing edge type dimmer requires the neutral wire for installation.

**Bitte beachten:**

- Die Kompatibilitätsliste basiert auf Tests, die der Hersteller in einer im Labor simulierten Umgebung durchgeführt hat. Die Ergebnisse können aufgrund verschiedener Faktoren in manchen Praxisanwendungen abweichen. OSRAM übernimmt keinerlei Verantwortung, Garantie oder Haftung dafür, dass diese Ergebnisse tatsächlich mit den Geräten unter anderen Bedingungen, mit Nachfolgemodellen der getesteten Geräte, mit anderen Modellen desselben Herstellers oder bei Verwendung anderer LED-Lampentypen erreicht werden.
- Das Fehlen eines Dimmers in der Abbildung bedeutet nicht, dass ein Dimmer nicht kompatibel ist.
- Lesen Sie stets die Installationsanweisungen des Dimmerherstellers.
- LED-Lampen bestehen aus mehreren elektronischen Komponenten. Unter ungünstigen Bedingungen können diese Störgeräusche erzeugen. Im Resonanzfall können selbst geringe Geräusche einen hörbaren Effekt hervorrufen. Einflussfaktoren können die Installation, die Gestaltung des Lampenträgers, die Leuchte (akustischer Resonanzeffekt), der Dimmer oder der Trafo (Oberschwingungen oder elektronische Resonanz) sein.
- Änderungen vorbehalten.
- Irrtümer und Auslassungen vorbehalten.
- Vergewissern Sie sich, dass Sie stets die aktuellste Version benutzen.

**Anwendungshinweis:**

- Um bestmögliche Dimmergebnisse zu erzielen, wird die Verwendung von Phasenabschnitt-Dimmern empfohlen.
- Phasenabschnitt-Dimmer erfordern bei der Installation einen Neutralleiter.

**LEDVANCE GmbH**

Head Office:

Parkring 29-33  
85748 Garching, Germany  
Phone +49 89 780673-100  
Fax +49 89 780673-XXX  
[www.ledvance.com](http://www.ledvance.com)