

DIMMER COMPATIBILITY PERFORMANCE MR16

BASIC INFORMATION:

1. WHAT IS THE PRODUCT CODE AND WHERE DO I FIND IT?

The product code describes the lamp type. It contains 7 letters and digits and is starting with "A". Below an example for the product code of the stamp of the lamp:



12 V **AC10137** 2700K
5 W 50/60 Hz 440 mA
Made in Germany XXX-XXXX

2. HOW CAN I READ THE FOLLOWING CHARTS?

Legend:
Information about the dimmability of the lamps. Green means very good dimmability, yellow means limited dimmability, red means undesired dimmability etc.

List of dimmers tested in laboratory conditions

Legend					PARATHOM DIM CLP 25 Glass Frosted				PARATHOM DIM CLP 25 FIL				PARATHOM DIM CLP 40 Frosted				PARATHOM DIM CLP 40			
Very good dimmability with indicated number of lamps (dimming range greater than 75%)					lamm		lamm		lamm		lamm		lamm		lamm		lamm		lamm	
Limited dimmability with indicated number of lamps (dimming range smaller than 75%)					lamm		lamm		lamm		lamm		lamm		lamm		lamm		lamm	
Undesired dimmability					lamm		lamm		lamm		lamm		lamm		lamm		lamm		lamm	
Not relevant					lamm		lamm		lamm		lamm		lamm		lamm		lamm		lamm	
Dimmer					Dimming		Dimming		Dimming		Dimming		Dimming		Dimming		Dimming		Dimming	
Brand	Model	Voltage range	Power	Type	range 1	range 4	range 1	range 4	range 1	range 4	range 1	range 4	range 1	range 4	range 1	range 4	range 1	range 4	range 1	range 4
ABB	STD 50-3	230/50Hz	60-500	L	89-3%	100-5%	89-3%	100-5%					88-2%	99-5%						
Altenburger	50_3	230/50Hz	400	R	100-3%	100-3%	100-3%	100-3%					97-2%	97-2%						
AURORA	DSP 400	230/50Hz	400	R																
Berker	2861	230/50Hz	50-420	U	96-10%	99-8%	96-10%	99-8%	96-0%	96-0%			100-1%	99-9%						
bticino	NT4402N	230/50Hz	500	R					96-4%	96-4%				85-2%						
Bticino	NT4408HC/HD/HS4+	230/50Hz			100-3%	100-3%	100-3%	100-3%	94-0%	96-0%			97-1%	97-1%						
Bticino	L/N/NT4411N	230/50Hz			100-3%	100-3%	100-3%	100-3%	94-9%	96-3%			94-1%	97-2%						
Busch-Jaeger	2250 U	230/50Hz	60-600	L		40-3%		40-3%												
Busch-Jaeger	6513 U-102	230/50Hz	420	T		100-3%		100-3%					97-6%	97-1%						
Busch-Jaeger	6526 U	230/50Hz			100-12%	100-3%	100-12%	100-3%					96-1%	99-5%						
Busch-Jaeger	6523 U-102	230/50Hz	40-420	T		100-13%		100-13%					96-6%	97-1%						
CENTURY CONTROL	MULTI DIMMER	230/50Hz	60-600	U	95-3%	99-3%	95-3%	99-3%						96-1%						
DINUY	RE L1 LE1	230/50Hz	400	LED	100-3%	100-3%	100-3%	100-3%	96-4%	96-4%			100-1%	100-2%						
ELKO	400GLE	230/50Hz				93-3%		93-3%						85-2%						
ELKO	315GLE	230/50Hz	20-	T		100-3%		100-3%						96-2%						
ELKO	600GLI	230/50Hz	40-600	U	100-3%	100-6%	100-3%	100-6%					99-2%	100-2%						
ELKO	420GLE/I	230/50Hz	40-420	U		101-3%		101-3%					94-6%	97-2%						

Information about the OSRAM lamp type

Assessment of the results into categories. Includes the number of lamps and the related dimming range

DIMMER KOMPATIBILITÄT PERFORMANCE MR16

BASISINFORMATIONEN:

1. WAS IST DER PRODUKTCODE UND WO FINDE ICH IHN?

Der Produktcode beschreibt den Lampentyp. Er besteht aus sieben Buchstaben und Ziffern und beginnt mit einem "A". Nachfolgend ein Beispiel eines Produktcodes auf dem Aufdruck der Lampe.



12 V **AC10137** 2700K
5 W 50/60 Hz 440 mA
Made in Germany XXX-XXXX

2. WIE LESE ICH DIE FOLGENDEN TABELLEN?

Legende: Angaben zur Dimmbarkeit der Lampen. Grün bedeutet eine sehr gute Dimmbarkeit mit der angegebenen Lampenanzahl, gelb bedeutet eine eingeschränkte Dimmbarkeit, rot bedeutet, dass unerwünschtes dimmverhalten auftreten kann etc.



Liste der getesteten Dimmer

Legend					PARATHOM DIM CLP			
					2.5 Glass Frosted	2.5 FIL	40 Frosted	40
Very good dimmability with indicated number of lamps (dimming range at least 75%)								
Limited dimmability with indicated number of lamps (dimming range at least 75%)								
Undesired dimmability								
Not relevant								
Dimmer					OSRAM Basic Code	OSRAM Basic Code	OSRAM Basic Code	OSRAM Basic Code
Brand	Model	Voltage range	Power	Type	100-0-100%	100-0-100%	100-0-100%	100-0-100%
ABB	STO 50-3	230/50 Hz	60-500 L	L	100-0-100%	100-0-100%	100-0-100%	100-0-100%
AURORA	S.O.3	230/50 Hz			100-0-100%	100-0-100%	100-0-100%	100-0-100%
AURORA	OSP 400	230/50 Hz	400 R	R	95-10%	95-4%	95-10%	95-0%
Berker	2861	230/50 Hz	50-420 U	U	100-0-100%	100-0-100%	100-0-100%	100-0-100%
Bidino	NT44 02 IN	230/50 Hz	500 R	R	100-0-100%	100-0-100%	100-0-100%	100-0-100%
Bidino	NT44 04HC (40/45A)	230/50 Hz	500 R	R	100-0-100%	100-0-100%	100-0-100%	100-0-100%
Bidino	L/N/NT44 11N	230/50 Hz			100-0-100%	100-0-100%	100-0-100%	100-0-100%
Schwaiger	21 50 U	230/50 Hz	60-600 L	L	100-0-100%	100-0-100%	100-0-100%	100-0-100%
Schwaiger	6 51 3 U-10 2	230/50 Hz	420 T	T	100-0-100%	100-0-100%	100-0-100%	100-0-100%
Schwaiger	66 28 U	230/50 Hz			100-0-100%	100-0-100%	100-0-100%	100-0-100%
Schwaiger	6 51 3 U-10 2	230/50 Hz	40-420 T	T	100-0-100%	100-0-100%	100-0-100%	100-0-100%
CEINSTEIN	MSL 210/10/10R	230/50 Hz	60-600 U	U	100-0-100%	100-0-100%	100-0-100%	100-0-100%
DIMBY	66 61 L	230/50 Hz	400 LED	LED	100-0-100%	100-0-100%	100-0-100%	100-0-100%
ELKO	40 0GLI	230/50 Hz			100-0-100%	100-0-100%	100-0-100%	100-0-100%
ELKO	215 0GL	230/50 Hz	30- T	T	100-0-100%	100-0-100%	100-0-100%	100-0-100%
ELKO	60 0GLI	230/50 Hz	40-600 U	U	100-0-100%	100-0-100%	100-0-100%	100-0-100%
ELKO	42 0GLI	230/50 Hz	40-420 U	U	100-0-100%	100-0-100%	100-0-100%	100-0-100%



Angaben zum OSRAM Lampentyp

Bewertung der Testergebnisse in Ampel Kategorien. Beinhaltet sowohl die Lampenanzahl als auch den dimmbaren Bereich



DIMMER COMPATIBILITY PERFORMANCE MR16

Legend					PERFORMANCE MR16 35 36°		PERFORMANCE MR16 50 36°	
Very good dimmability with indicated number of lamps (dimming range greater than 75%)					 EAN / Basic Code		 EAN / Basic Code	
Limited dimmability with indicated number of lamps (dimming range smaller than 75%)								
Undesired dimmability								
Not tested								
Connect with LVED VAL 20/220-240/12					4058075165535 / AC10137 4058075165618 / AC10138 4058075165632 / AC10139 4058075165557 / AC10135 4058075165571 / AC10136		4058075165656 / AC10141 4058075165670 / AC10142 4058075166011 / AC10146 4058075187436 / AC10146 4058075166042 / AC10147 4058075166073 / AC10148 4058075165694 / AC10143 4058075165717 / AC10144 4058075165953 / AC10144 4058075165731 / AC10145 4058075165984 / AC10145	
Dimmer					Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps
Brand	Model	Voltage range	Power	Type				
TCL-Legrand	V8051-M	230/50Hz	40-630W	L	0-100%	0-100%	0-100%	0-100%
Schneider-Clipsal	KB31RD400	230/50Hz	400W	L	0-100%	0-100%	0-100%	0-100%
Siemens	5UH8622-3NC01	230/50Hz	25-400W	L	0-100%	0-100%	0-100%	0-100%
Schneider-Electric	C460	230/50Hz	400W	L	0-100%	0-100%	0-100%	0-100%
Schneider-Electric	U201DST600	230/50Hz	40-600VA	L	0-100%	0-99%	0-100%	0-98%
Honyar	KT250	230/50Hz	15-250W	L	0-100%	0-100%	0-100%	0-100%
Schneider-Electric	40600 RL	230/50Hz	40-600W	L	0-100%	0-100%	0-100%	0-100%
Lutron	GXI-3104-T-CE-WH	230/50Hz	2300W	T	3-100%	0-99%	0-100%	0-100%
Panasonic	WMS549	230/50Hz	40-400W	L	0-100%	0-100%	0-100%	0-100%
Siemens	5UH8122-3NC01	230/50Hz	25-400W	L	0-100%	0-99%	0-100%	0-100%
Schneider-Clipsal	E8431EPD4	230/50Hz	25-350W	L	0-100%	0-100%	17-100%	0-100%
MK branded	K1541 WHI	230/50Hz	75-500W	T	0-100%	0-100%	0-84%	0-100%
Veto	VT-500	230/50Hz	60-500W	T	0-94%	0-100%	0-84%	0-100%
Legrand	617030	230/50Hz	600W	L	0-100%	0-100%	0-100%	0-100%
Dynalite	DMC810GL	230/50Hz	channels 1	L	0-100%	0-100%	0-100%	0-100%





DIMMER COMPATIBILITY PERFORMANCE MR16

Legend					PERFORMANCE MR16 35 36°		PERFORMANCE MR16 50 36°	
Very good dimmability with indicated number of lamps (dimming range greater than 75%)								
Limited dimmability with indicated number of lamps (dimming range smaller than 75%)								
Undesired dimmability					EAN / Basic Code		EAN / Basic Code	
Not tested					4058075165595 / AC10137 4058075165618 / AC10138 4058075165632 / AC10139 4058075165557 / AC10135 4058075165571 / AC10136		4058075165656 / AC10141 4058075165670 / AC10142 4058075166011 / AC10146 4058075167436 / AC10146 4058075166042 / AC10147 4058075166073 / AC10148 4058075165694 / AC10143 4058075165717 / AC10144	
Connect with LVED VAL 20/220-240/12 CE								
Dimmer					Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps
Brand	Model	Voltage range	Power	Type				
LUMEX	LOADSMART LT1D450LS	230/50Hz	500VA	L	0-100%	0-100%	0-100%	0-100%
Schneider-Clipsal	KB31RD400	230/50Hz	400W	L	0-100%	0-100%	0-100%	0-100%
Clipsal	32E450UDM	230/50Hz	450W	T	24-100%	13-100%	19-100%	10-100%
HPM	CAT400T HPM	230/50Hz	400W	T	0-100%	4-100%	8-100%	3-100%
Anam / Legrand	ASW3000H	230/50Hz	1000W	T	44-100%	12-100%	27-100%	10-96%
Trader	Dimpala	230/50Hz	400W	U	0-100%	0-100%	0-100%	0-100%
Clipsal	32ELEDM	230/50Hz	400W	LED	0-100%	0-100%	0-100%	0-100%
Clipsal	32E450LM	230/50Hz	450W	L	0-100%	0-100%	0-100%	0-100%
HPM	CAT400L	230/50Hz	400W	L	12-100%	9-100%	9-100%	6-100%
Panasonic	WMS549	230/50Hz	40-400W	L	0-100%	0-100%	0-100%	0-100%
SAL	SDA450	230/50Hz	450W	T	15-100%	7-100%	10-100%	4-100%
MK branded	K1541 WHI	230/50Hz	75-500W	T	0-100%	0-100%	0-100%	0-85%
Veto	VT-500	230/50Hz	60-500W	T	7-100%	0-69%	0-100%	0-100%
DIGINET(GERARD)	MMDM/PB	230/50Hz	400W	Push Button	0-0%	0-100%	0-100%	0-100%
Panasonic	WEG 57912	230/50Hz	40-200W	L	0-100%	0-100%	0-100%	0-100%
SR SANJOON	SRD-1000	230/50Hz	1000W	L	24-100%	0-100%	13-100%	0-100%
JIN HEUNG ELECTRIC	JH-922473	230/50Hz	1000W	L	8-100%	0-100%	0-100%	0-100%









DIMMER COMPATIBILITY PERFORMANCE MR16

Legend						PERFORMANCE MR16 35 36°		PERFORMANCE MR16 50 36°	
Very good dimmability with indicated number of lamps (dimming range greater than 75%)									
Limited dimmability with indicated number of lamps (dimming range smaller than 75%)									
Undesired dimmability						EAN / Basic Code		EAN / Basic Code	
Not tested									
Connect with LVED VAL 40/230-240/12 CE						4058075165595 / AC10137 4058075165618 / AC10138 4058075165632 / AC10139 4058075165557 / AC10135 4058075165571 / AC10136		4058075165656 / AC10141 4058075165670 / AC10142 4058075166011 / AC10146 4058075187436 / AC10146 4058075166042 / AC10147 4058075166073 / AC10148	
Dimmer						Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps
Brand	Model	Voltage range	Power	Type					
LUMEX	LOADSMART LT1D450LS	230/50Hz	500VA	L	0-100%	0-99%	0-100%	0-99%	
Clipsal	32E450UDM	230/50Hz	450W	T	26-100%	15-100%	20-100%	12-100%	
HPM	CAT400T HPM	230/50Hz	400W	T	11-100%	6-100%	10-100%	0-100%	
Trader	Dimpala	230/50Hz	400W	U	0-100%	0-100%	0-100%	0-100%	
Clipsal	32ELEDM	230/50Hz	400W	LED	0-100%	0-100%	0-100%	0-100%	
Clipsal	32E450LM	230/50Hz	450W	L	0-99%	0-100%	0-100%	0-100%	
HPM	CAT400L	230/50Hz	400W	L	8-100%	9-100%	8-100%	5-100%	
SAL	SDA450	230/50Hz	450W	T	18-100%	8-100%	13-100%	7-100%	
DIGINET(GERARD)	MMDM/PB	230/50Hz	400W	Push Button	0-100%	0-99%	0-100%	0-100%	









DIMMER COMPATIBILITY PERFORMANCE MR16

Legend						PERFORMANCE MR16 35 36*		PERFORMANCE MR16 50 36*		PARATHOM PRO MR16 35 36*		PARATHOM PRO MR16 43 36*	
Very good dimmability with indicated number of lamps (dimming range greater than 75%)													
Limited dimmability with indicated number of lamps (dimming range smaller than 75%)						EAN / Basic Code		EAN / Basic Code		EAN / Basic Code		EAN / Basic Code	
Undesired dimmability													
Not tested													
Connect with OSRAM ET-L 30/220-240						4058075165595 / AC10137 4058075165618 / AC10138 4058075165632 / AC10139 4058075165557 / AC10135 4058075165571 / AC10136		4058075165656 / AC10141 4058075165670 / AC10142 4058075166011 / AC10146 4058075187436 / AC10146 4058075166042 / AC10147 4058075166073 / AC10148 4058075165634 / AC10143 4058075165717 / AC10144 4058075165953 / AC10144 4058075165731 / AC10145 4058075165984 / AC10145		4058075094934 / AC07564 4058075094970 / AC07565		4058075095069 / AC07567 4058075095045 / AC07568	
						Dimmer						Dimming range 1Lamp	Dimming range 4 Lamps
Brand	Model	Voltage range	Power	Type									
TCL-Legrand	V8051-M	230/50Hz	40-630W	L		0-100%	0-100%	1-100%	1-100%	0-99%	0-99%	0-99%	0-99%
Panasonic	WEG57813	230/50Hz	40-300W	L		0-98%	0-100%	0-100%	0-100%	0-99%	0-99%	0-98%	0-99%
LUMEX	.OADMART LT1D450LS	230/50Hz	500VA	L		0-100%	0-100%	0-100%	0-100%	0-99%	0-99%	0-99%	0-99%
Schneider-Clipsal	KB31RD400	230/50Hz	400W	L		0-100%	0-100%	1-100%	1-100%	0-99%	0-99%	0-99%	0-99%
Clipsal	32E450UDM	230/50Hz	450W	T		6-100%	4-100%	5-100%	4-100%	9-99%	10-99%	9-99%	7-99%
HPM	CAT400T HPM	230/50Hz	400W	T		0-100%	0-100%	1-100%	1-100%	0-99%	0-99%	0-99%	0-98%
Anam / Legrand	ASW3000H	230/50Hz	1000W	T		5-100%	28-100%	16-100%	16-100%	0-99%	0-99%	0-99%	0-99%
Trader	Dimpala	230/50Hz	400W	U		0-100%	0-100%	0-100%	0-100%	6-99%	0-99%	6-99%	0-99%
Clipsal	32ELEDM	230/50Hz	400W	LED		0-100%	0-100%	0-100%	0-100%	0-100%	0-94%	0-100%	0-85%
Siemens	5UH8622-3NC01	230/50Hz	25-400W	L		0-59%	6-100%	6-100%	16-100%	0-100%	7-98%	0-96%	7-87%
Schneider-Electric	C460	230/50Hz	400W	L		0-100%	0-100%	0-100%	0-100%	0-100%	0-100%	0-100%	0-89%
Schneider-Electric	U201DST600	230/50Hz	40-600VA	L		9-100%	0-100%	4-100%	0-100%	0-100%	0-75%	4-93%	0-67%
Clipsal	32E450LM	230/50Hz	450W	L		0-100%	0-100%	0-100%	0-100%	4-100%	0-99%	0-100%	0-90%
Honyar	KT250	230/50Hz	15-250W	L		0-100%	1-100%	1-100%	1-100%	0-100%	0-99%	0-100%	0-89%
Schneider-Electric	40600 RL	230/50Hz	40-600W	L		11-100%	16-100%	18-100%	18-100%	0-100%	10-89%	10-99%	9-83%





DIMMER COMPATIBILITY PERFORMANCE MR16

Legend					PERFORMANCE MR16 35 36°	PERFORMANCE MR16 50 36°	PARATHOM PRO MR16 35 36°	PARATHOM PRO MR16 43 36°				
 Very good dimmability with indicated number of lamps (dimming range greater than 75%)  Limited dimmability with indicated number of lamps (dimming range smaller than 75%)  Undesired dimmability  Not tested												
Connect with OSRAM ET-L 30/220-240					EAN / Basic Code	EAN / Basic Code	EAN / Basic Code	EAN / Basic Code				
					4058075165595 / AC10137 4058075165618 / AC10138 4058075165632 / AC10139 4058075165557 / AC10135 4058075165571 / AC10136	4058075165656 / AC10141 4058075165670 / AC10142 4058075166011 / AC10146 4058075187436 / AC10146 4058075166042 / AC10147 4058075166073 / AC10148 4058075165694 / AC10143 4058075165717 / AC10144 4058075165953 / AC10144	4058075034994 / AC07564 4058075034970 / AC07565	4058075035069 / AC07567 4058075035045 / AC07568				
Dimmer					Dimming range 1Lamp	Dimming range 4 Lamps	Dimming range 1Lamp	Dimming range 4 Lamps	Dimming range 1Lamp	Dimming range 4 Lamps	Dimming range 1Lamp	Dimming range 4 Lamps
Brand	Model	Voltage range	Power	Type								
Step	E033	230/50Hz	45-300W	L	0-100%	0-100%	0-100%	0-100%	0-99%	0-99%	0-100%	0-91%
Bticino	SAMS350	230/50Hz	40-300W	L	0-100%	0-100%	0-100%	0-100%	0-99%	0-99%	0-99%	0-91%
Lutron	GXI-3104-T-CE-WH	230/50Hz	2300W	T	0-100%	0-100%	2-100%	2-100%	6-99%	2-99%	0-100%	0-84%
HPM	CAT400L	230/50Hz	400W	L	8-100%	0-100%	0-100%	0-100%	12-99%	7-99%	8-96%	4-74%
Panasonic	WMS549	230/50Hz	40-400W	L	0-100%	0-100%	0-100%	1-100%	0-99%	0-99%	0-100%	0-88%
SAL	SDA450	230/50Hz	450W	T	23-100%	15-100%	17-100%	17-100%	22-100%	19-99%	16-100%	16-100%
Siemens	SUH8122-3NC01	230/50Hz	25-400W	L	0-66%	6-100%	2-100%	17-100%	0-100%	17-99%	0-96%	14-100%
Schneider-Clipsal	E8431EPD4	230/50Hz	25-350W	L	0-100%	0-100%	0-100%	0-100%	0-100%	0-99%	0-99%	0-100%
MK branded	K1541 WHI	230/50Hz	75-500W	T	0-100%	0-100%	0-100%	0-100%	0-78%	0-92%	0-56%	0-88%
Veto	VT-500	230/50Hz	60-500W	T	0-79%	0-100%	1-100%	0-100%	0-96%	0-99%	0-67%	0-100%
DIGINET(GERARD)	MMDM/PB	230/50Hz	400W	Push Button	0-99%	0-100%	0-100%	0-100%	0-100%	0-99%	0-100%	0-100%
Legrand	617030	230/50Hz	600W	L	0-100%	0-100%	0-100%	0-100%	0-100%	0-99%	0-99%	0-100%
Panasonic	WEG 57912	230/50Hz	40-200W	L	12-100%	8-100%	0-100%	0-100%	17-100%	11-100%	15-99%	11-99%
SR SANJOON	SRD-1000	230/50Hz	1000W	L	0-100%	16-100%	7-100%	17-100%	12-99%	16-100%	9-99%	13-99%
JIN HEUNG ELECTRIC	JH-922473	230/50Hz	1000W	L	0-100%	6-100%	5-100%	8-100%	10-99%	9-100%	9-100%	9-99%
Dynalite	DMC810GL	230/50Hz	channels 1	L	0-100%	0-100%	0-100%	0-100%	0-99%	0-99%	0-99%	0-99%





DIMMER COMPATIBILITY PERFORMANCE MR16

Legend					PERFORMANCE MR16 35 36°		PERFORMANCE MR16 50 36°		PARATHOM PRO MR16 35 36°		PARATHOM PRO MR16 43 36°	
 Very good dimmability with indicated number of lamps (dimming range greater than 75%)												
 Limited dimmability with indicated number of lamps (dimming range smaller than 75%)					EAN / Basic Code		EAN / Basic Code		EAN / Basic Code		EAN / Basic Code	
 Undesired dimmability					4058075165595 / AC10137 4058075165618 / AC10138 4058075165632 / AC10139 4058075165557 / AC10135 4058075165571 / AC10136		4058075165656 / AC10141 4058075165670 / AC10142 4058075166011 / AC10146 4058075187436 / AC10146 4058075166042 / AC10147 4058075166073 / AC10148 4058075165694 / AC10143 4058075165717 / AC10144 4058075165953 / AC10144 4058075165731 / AC10145 4058075165384 / AC10145		4058075094994 / AC07564 4058075094970 / AC07565		4058075095069 / AC07567 4058075095045 / AC07568	
 Not tested												
Connect with OSRAM ET-A 60/220-240												
Dimmer					Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps
Brand	Model	Voltage range	Power	Type								
TCL-Legrand	V8051-M	230/50Hz	40-630W	L	0-100%	0-100%	0-100%	0-100%	0-99%	0-99%	0-99%	0-99%
Panasonic	WEG57813	230/50Hz	40-300W	L	0-46%	0-100%	0-100%	0-100%	0-99%	0-99%	0-93%	0-99%
LUMEX	LOADSMART LT1D450LS	230/50Hz	500VA	L	0-100%	0-100%	0-100%	0-100%	0-99%	0-99%	0-99%	0-99%
Schneider-Clipsal	KB31RD400	230/50Hz	400W	L	0-100%	0-100%	0-100%	0-100%	0-99%	0-99%	0-99%	0-99%
Clipsal	32E450UDM	230/50Hz	450W	T	3-100%	6-100%	7-100%	7-100%	4-99%	8-99%	5-99%	6-99%
HPM	CAT400T HPM	230/50Hz	400W	T	0-100%	0-100%	1-100%	1-100%	0-99%	0-99%	0-98%	0-98%
Anam / Legrand	ASW3000H	230/50Hz	1000W	T	0-84%	6-100%	18-100%	20-100%	0-99%	0-99%	0-99%	0-99%
Trader	Dimpala	230/50Hz	400W	U	0-100%	0-100%	0-100%	0-100%	6-99%	4-99%	0-99%	0-80%
Clipsal	32ELEDM	230/50Hz	400W	LED	0-100%	0-100%	0-100%	0-100%	0-100%	0-90%	0-99%	0-81%
Siemens	5UH8622-3NC01	230/50Hz	25-400W	L	0-100%	4-100%	7-100%	6-100%	0-100%	0-96%	0-100%	0-87%
Schneider-Electric	C460	230/50Hz	400W	L	0-100%	0-100%	0-100%	0-100%	0-100%	0-96%	0-100%	0-66%
Schneider-Electric	U201DST600	230/50Hz	40-600VA	L	10-100%	0-100%	4-100%	0-100%	4-97%	0-72%	3-88%	0-86%
Clipsal	32E450LM	230/50Hz	450W	L	0-100%	0-100%	0-100%	0-100%	0-100%	0-93%	0-100%	0-85%
Honyar	KT250	230/50Hz	15-250W	L	0-100%	0-100%	0-100%	0-100%	0-100%	0-93%	0-100%	0-77%
Schneider-Electric	40600 RL	230/50Hz	40-600W	L	0-100%	0-100%	0-100%	0-100%	0-100%	0-81%	0-95%	18-100%








DIMMER COMPATIBILITY PERFORMANCE MR16

Legend					PERFORMANCE MR16 35 36*		PERFORMANCE MR16 50 36*		PARATHOM PRO MR16 35 36*		PARATHOM PRO MR16 43 36*	
Very good dimmability with indicated number of lamps (dimming range greater than 75%)												
Limited dimmability with indicated number of lamps (dimming range smaller than 75%)					EAN / Basic Code		EAN / Basic Code		EAN / Basic Code		EAN / Basic Code	
Undesired dimmability												
Not tested												
Connect with OSRAM ET-A 60/220-240					4058075165535 / AC10137 4058075165618 / AC10138 4058075165632 / AC10139 4058075165557 / AC10135 4058075165571 / AC10136		4058075165656 / AC10141 4058075165670 / AC10142 4058075166011 / AC10146 4058075167436 / AC10146 4058075166042 / AC10147 4058075166073 / AC10148 4058075165634 / AC10143 4058075165717 / AC10144 4058075165353 / AC10144 4058075165731 / AC10145 4058075165384 / AC10145		4058075034934 / AC07564 4058075034970 / AC07565		4058075035069 / AC07567 4058075035045 / AC07568	
Dimmer					Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps
Brand	Model	Voltage range	Power	Type								
Step	E033	230/50Hz	45-300W	L	0-100%	0-100%	0-100%	0-100%	0-100%	0-96%	0-92%	0-88%
Bticino	SAM5350	230/50Hz	40-300W	L	0-100%	0-100%	0-100%	0-100%	0-99%	0-97%	0-100%	0-89%
Lutron	GXI-3104-T-CE-WH	230/50Hz	2300W	T	0-100%	0-100%	3-100%	3-100%	0-100%	2-99%	0-100%	0-81%
HPM	CAT400L	230/50Hz	400W	L	0-100%	0-100%	6-100%	0-100%	0-99%	0-99%	0-78%	0-66%
Panasonic	WMS549	230/50Hz	40-400W	L	0-100%	0-100%	0-100%	0-100%	0-99%	0-99%	0-100%	0-87%
SAL	SDA450	230/50Hz	450W	T	19-100%	17-100%	20-100%	18-100%	23-100%	12-99%	14-100%	18-100%
Siemens	5UH8122-3NC01	230/50Hz	25-400W	L	0-100%	4-100%	7-100%	5-100%	0-100%	0-99%	0-100%	0-100%
Schneider-Clipsal	E8431EPD4	230/50Hz	25-350W	L	0-100%	0-100%	0-100%	2-100%	0-100%	0-99%	0-92%	0-100%
MK branded	K1541 WHI	230/50Hz	75-500W	T	0-71%	0-100%	0-100%	0-100%	0-66%	0-97%	0-45%	0-82%
Veto	VT-500	230/50Hz	60-500W	T	0-100%	0-100%	0-100%	0-100%	0-99%	0-99%	0-82%	0-99%
DIGINET(GERARD)	MMDM/PB	230/50Hz	400W	Push Button	0-100%	0-100%	0-100%	0-100%	0-100%	0-99%	0-98%	0-100%
Legrand	617030	230/50Hz	600W	L	0-100%	0-100%	0-100%	0-100%	0-99%	0-99%	0-99%	0-100%
Panasonic	WEG 57912	230/50Hz	40-200W	L	12-100%	8-100%	0-100%	0-100%	15-100%	10-100%	15-99%	10-99%
SR SANJOON	SRD-1000	230/50Hz	1000W	L	5-100%	4-100%	6-100%	6-100%	0-99%	0-100%	0-99%	7-99%
JIN HEUNG ELECTRIC	JH-922473	230/50Hz	1000W	L	1-100%	0-100%	1-100%	1-100%	0-99%	0-100%	0-99%	0-99%
Dynalite	DMC810GL	230/50Hz	channels 1	L	0-100%	0-100%	0-100%	0-100%	0-99%	0-99%	0-99%	0-99%



DIMMER COMPATIBILITY PERFORMANCE MR16

Legend					PERFORMANCE MR16 35 36°		PERFORMANCE MR16 50 36°		PARATHOM PRO MR16 35 36°		PARATHOM PRO MR16 43 36°	
Very good dimmability with indicated number of lamps (dimming range greater than 75%)												
Limited dimmability with indicated number of lamps (dimming range smaller than 75%)					EAN / Basic Code		EAN / Basic Code		EAN / Basic Code		EAN / Basic Code	
Undesired dimmability					4058075165535 / AC10137 4058075165618 / AC10138 4058075165632 / AC10139 4058075165557 / AC10135 4058075165571 / AC10136		4058075165656 / AC10141 4058075165670 / AC10142 4058075166011 / AC10146 4058075167436 / AC10146 4058075166042 / AC10147 40580751666073 / AC10148		4058075034934 / AC07564 4058075034970 / AC07565		4058075035069 / AC07567 4058075035045 / AC07568	
Not tested												
Connect with ET-REDBBACK 40VA/230-20												
Dimmer					Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps
Brand	Model	Voltage range	Power	Type								
LUMEX	LOADSMART LT1D450LS	230/50Hz	500VA	L	0-99%	0-100%	0-100%	0-100%	0-99%	0-99%	0-99%	0-99%
Clipsal	32E450UDM	230/50Hz	450W	T	14-100%	11-100%	13-100%	13-100%	19-99%	13-99%	15-99%	12-99%
HPM	CAT400T HPM	230/50Hz	400W	T	0-100%	0-100%	3-100%	2-100%	7-99%	0-99%	7-99%	0-99%
Trader	Dimpala	230/50Hz	400W	U	0-100%	0-100%	0-100%	0-100%	0-99%	0-99%	0-99%	0-99%
Clipsal	32ELEDM	230/50Hz	400W	LED	/	/	1-100%	1-100%	0-100%	0-100%	0-100%	0-92%
Clipsal	32E450LM	230/50Hz	450W	L	0-100%	0-100%	0-100%	0-100%	0-100%	0-99%	0-99%	0-99%
HPM	CAT400L	230/50Hz	400W	L	6-100%	6-100%	3-100%	4-100%	14-99%	11-99%	0-78%	0-77%
SAL	SDA450	230/50Hz	450W	T	10-100%	8-100%	10-100%	8-100%	17-100%	10-99%	10-100%	9-93%
DIGINET(GERARD)	MMDM/PB	230/50Hz	400W	Push Button	0-100%	0-100%	0-100%	0-100%	0-100%	0-99%	0-100%	0-92%

DIMMER COMPATIBILITY PERFORMANCE MR16

Legend					PERFORMANCE MR16 35 36°		PERFORMANCE MR16 50 36°		PARATHOM PRO MR16 35 36°		PARATHOM PRO MR16 43 36°	
 Very good dimmability with indicated number of lamps (dimming range greater than 75%)												
 Limited dimmability with indicated number of lamps (dimming range smaller than 75%)												
 Undesired dimmability					EAN / Basic Code		EAN / Basic Code		EAN / Basic Code		EAN / Basic Code	
Not tested												
Connect with ET-HTM 70W/230-240					4058075165535 / AC10137 4058075165618 / AC10138 4058075165632 / AC10139 4058075165557 / AC10135 4058075165571 / AC10136		4058075165656 / AC10141 4058075165670 / AC10142 4058075166011 / AC10146 4058075187436 / AC10146 4058075166042 / AC10147 4058075166073 / AC10148 4058075165694 / AC10143 4058075165717 / AC10144 4058075165953 / AC10144 4058075165731 / AC10145 4058075165984 / AC10145		4058075034994 / AC07564 4058075034970 / AC07565		4058075095069 / AC07567 4058075095045 / AC07568	
Dimmer					Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps
Brand	Model	Voltage range	Power	Type								
Shuttle	SDIM-T-LED 500W	230/50Hz	500W	T	0-100%	5-100%	3-100%	1-100%	3-100%	4-99%	0-100%	0-88%
Shuttle	SDIMR-T-LED 500W	230/50Hz	500W	T	0-100%	0-100%	2-100%	3-100%	0-100%	0-100%	0-100%	0-86%
Shuttle	SDIM-T-LED 125W	230/50Hz	125W	T	0-100%	0-100%	2-100%	0-100%	0-100%	0-100%	0-100%	0-87%
OSRAM	Hti DALI 315/230-240 DIM	230/50Hz	35-105W	Hti	8-100%	7-100%	6-98%	5-99%	5-100%	0-100%	5-100%	0-100%

DIMMER COMPATIBILITY PERFORMANCE MR16

Legend					PARATHOM PRO MR16 35 36°		PARATHOM PRO MR16 43 36°	
Very good dimmability with indicated number of lamps (dimming range greater than 75%)					 EAN / Basic Code		 EAN / Basic Code	
Limited dimmability with indicated number of lamps (dimming range smaller than 75%)								
Undesired dimmability								
Not tested								
Connect with ET-HTM 105W/230-240					4058075094994 / AC07564 4058075094970 / AC07565		4058075095069 / AC07567 4058075095045 / AC07568	
Dimmer					Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps
Brand	Model	Voltage range	Power	Type				
Shuttle	SDIM-T-LED 500W	230/50Hz	500W	T	4-100%	3-100%	0-100%	0-82%
Shuttle	SDIMR-T-LED 500W	230/50Hz	500W	T	0-100%	0-100%	0-100%	0-81%
Shuttle	SDIM-T-LED 125W	230/50Hz	125W	T	0-100%	0-99%	0-100%	0-82%

Please Note:

- The compatibility list is based upon testing conducted by the manufacturer in a lab simulated environment, and the results can vary in certain field applications due to a number of factors. OSRAM does not take over any responsibility, warranty or liability that this results can also achieved by using the devices under other conditions, or when using successor models of the tested devices, or different models of the same manufacturer, or when using other LED lamp types
- The absence of a dimmer from this chart does not necessarily imply incompatibility.
- Please reference the dimmer manufacturer's instructions for installation.
- LED lamps contain several electronic components. Under unfavourable conditions these can lead to acoustic noise. In case of resonance even low noise can cause audible effect. Possible factors influencing this are the installation, the design of the lamp holder and the luminaire (acoustic resonance effect) as well as the dimmer or the transformer (harmonics or electronic resonance).
- Subject to change without notice
- Errors and omission excepted
- Always make sure to use the most recent release

Application Notes:

- For best dimming results trailing edge dimmer type is recommended.
- Trailing edge type dimmer requires the neutral wire for installation.

Bitte beachten:

- Die Kompatibilitätsliste basiert auf Tests, die der Hersteller in einer im Labor simulierten Umgebung durchgeführt hat. Die Ergebnisse können aufgrund verschiedener Faktoren in manchen Praxisanwendungen abweichen. OSRAM übernimmt keinerlei Verantwortung, Garantie oder Haftung dafür, dass diese Ergebnisse tatsächlich mit den Geräten unter anderen Bedingungen, mit Nachfolgemodellen der getesteten Geräte, mit anderen Modellen desselben Herstellers oder bei Verwendung anderer LED-Lampentypen erreicht werden.
- Das Fehlen eines Dimmers in der Abbildung bedeutet nicht, dass ein Dimmer nicht kompatibel ist.
- Lesen Sie stets die Installationsanweisungen des Dimmerherstellers.
- LED-Lampen bestehen aus mehreren elektronischen Komponenten. Unter ungünstigen Bedingungen können diese Störgeräusche erzeugen. Im Resonanzfall können selbst geringe Geräusche einen hörbaren Effekt hervorrufen. Einflussfaktoren können die Installation, die Gestaltung des Lampenträgers, die Leuchte (akustischer Resonanzeffekt), der Dimmer oder der Trafo (Oberschwingungen oder elektronische Resonanz) sein.
- Änderungen vorbehalten.
- Irrtümer und Auslassungen vorbehalten.
- Vergewissern Sie sich, dass Sie stets die aktuellste Version benutzen.

Anwendungshinweis:

- Um bestmögliche Dimmergebnisse zu erzielen, wird die Verwendung von Phasenabschnitt-Dimmern empfohlen.
- Phasenabschnitt-Dimmer erfordern bei der Installation einen Neutralleiter.

LEDVANCE GmbH

Head Office:

Parkring 29-33
85748 Garching, Germany
Phone +49 89 780673-100
Fax +49 89 780673-XXX
www.ledvance.com