

SPECIAL PIN G4

Electric Transformer Compatibility

BASIC INFORMATION:

1. HOW CAN I UNDERSTAND THE FOLLOWING SHEETS?

- Compatibility to OSRAM ETs:
- Compatibility to OTHER ETs:

2. HOW MANY LAMPS CAN I INSTALL ON ONE ET?

For max. number of lamps on a ET, please use the following rule of thumb:
(Please note: actual number may vary from calculated result)


$$\frac{\text{Max load of ET}}{\text{equivalent wattage (HAL/GLS)}} = \text{max. number of lamps}$$

3. HOW CAN I READ THE FOLLOWING CHARTS?

Legend:
Information about the compatibility of the lamps and ETs. Green means very good habits, red means partial critical compatibility habits.

ET Compatibility traffic light system:	
Green	very good compatibility (no problems with ET)
Yellow	good compatibility habits (partially flickering)
Red	partial critical compatibility habits (flickering or darker light may occur)
White	not tested

STAR/ SUPERSTAR MR16 Electric Transformer Compatibility

Type	PARATHOM MR 11 20	PARATHOM ADV MR 11 20
	Product Picture	
EAN Product Code	4052899954977 AB 43472	4052899938667 AB 33561

Information about the OSRAM lamp type

Number of lamps tested on ET

List of ET being tested in the laboratory.

ET		Voltage range	Power	Type	Number of Lamps on ET:				Number of Lamps on ET:						
Brand	Model				1	2	3	4	1	2	3	4			
OSRAM	ET-LED30 /220-240	220-240, 50-60Hz	2-30W		Green	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green
OSRAM	HTM 70/230-240	230-240, 50-60Hz	20-70W		Green	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green
OSRAM	HTM 105/230-240	230-240, 50-60Hz	35-105W		Green	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green
OSRAM	ET-A 60/220-240	220-240, 50-60Hz	20-60W		Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red
OSRAM	ET-Z 60/220-240	220-240, 50-60Hz	20-60W		Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red
OSRAM	ET-Parrot 70/220-240 V/G	220-240, 50-60Hz	20-60W		Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red
OSRAM	ET-Parrot 105/220-240 V/G	220-240, 50-60Hz	35-105W		Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red
OSRAM	ET-P 60/220-240 (Gen 1)	220-240, 50-60Hz	20-60W		Green	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green
OSRAM	HTN 75/230-240 I	220-240, 50-60Hz	20-75W		Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red
OSRAM	ET-Redback 60/230-240	230-240, 50Hz	20-60W		Green	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green
OSRAM	ET-ZL50/220-240	220-240V 50/60HZ	50W		Green	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green
OSRAM	OT 30 220-240 12P	220-240V 50/60HZ	30W		Green	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green
OSRAM	OT 60 220-240 12P	220-240V 50/60HZ	60W		Green	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green

Test results of Compatibility according to the traffic light system

Example: ET ... works very well for one LED STAR MR16 20 lamp.

BASISINFORMATIONEN

1. WIE SIND DIE FOLGENDEN SEITEN ZU LESEN?

- Kompatibilität mit OSRAM ETs:
- Kompatibilität mit ANDEREN ETs :

2. WIE VIELE LAMPEN KANN ICH AN EINEN ET ANSCHLIESSEN?

Die maximale Anzahl an Lampen, die Sie an einen ET anschließen können, ergibt sich aus der folgenden Faustregel:

$$\frac{\text{Max load of ET equivalent wattage (HAL/GLS)}}{\text{max. number of lamps}} = \text{max. number of lamps}$$

3. WIE LESE ICH DIE FOLGENDEN TABELLEN?

Legende:
Angaben zur Kompatibilität der Lampen – grün bedeutet sehr gute Eigenschaften, rot bedeutet teilweise kritische Kompatibilität

ET Compatibility traffic light system:

- Green** very good compatibility (no problems with ET)
- Yellow** good compatibility habits (partially flickering)
- Red** partial critical compatibility habits (flickering or darker light may occur)
- White** not tested

STAR/ SUPERSTAR MR16 Electric Transformer Compatibility

Type	PARATHOM MR 11 20	PARATHOMADV MR 11 20
Product Picture		
EAN	4052899954977	4052899930687
Product Code	AB 43472	AB 33561

Angaben zum OSRAM-Lampentyp

ET				Number of Lamps on ET:			
Brand	Model	Voltage range	Power	1	2	3	4
OSRAM	ET-LED30 /220-240	220-240, 50-60Hz	2-30W	Green	Green	Green	Green
OSRAM	HTM 70/230-240	230-240, 50-60Hz	20-70W	Green	Green	Green	Green
OSRAM	HTM 105/230-240	230-240, 50-60Hz	35-105W	Green	Green	Green	Green
OSRAM	ET-A 60/220-240	220-240, 50-60Hz	20-80W	Green	Green	Green	Green
OSRAM	ET-Z 60/220-240	220-240, 50-60Hz	20-80W	Green	Green	Green	Green
OSRAM	ET-Parrot 70/220-240 I/G	220-240, 50-60Hz	20-80W	Red	Red	Red	Red
OSRAM	ET-Parrot 105/220-240 I/G	220-240, 50-60Hz	35-105W	Red	Red	Red	Red
OSRAM	ET-P 60/220-240 (Gen 1)	220-240, 50-60Hz	20-80W	Green	Green	Green	Green
OSRAM	HTN 75/230-240 I	220-240, 50-60Hz	20-75W	Green	Green	Green	Green
OSRAM	ET-Redback 60/230-240	230-240, 50Hz	20-80W	Green	Green	Green	Green
OSRAM	ET-ZL50/220-240	220-240V 50/60HZ	50W	Green	Green	Green	Green
OSRAM	OT 30 220-240 12P	220-240V 50/60HZ	30W	Green	Green	Green	Green
OSRAM	OT 60 220-240 12P	220-240V 50/60HZ	60W	Green	Green	Green	Green

Anzahl der an einem ET getesteten Lampen

Liste der getesteten ET

Ergebnisse des Kompatibilitätstests an der Lichtsignalanlage



Example: ET ... works very well for one LED STAR MR16 20 lamp.

OSRAM ETs

ET Compatibility traffic light system:

- Green** very good compatibility (no problems with ET)
- Yellow** good compatibility habits (partially flickering)
- Red** partial critical compatibility habits (flickering or darker light may occur)
- White** not tested

Lamp

Type	PIN G4 200 lm 1,7W	PIN G4 300 lm 2,4W
Product Picture		
EAN	4052899964358	4052899964372
Product Code	AB44659	AB44660



					ET									
Brand	Model	Voltage range	Power	Type	Number of Lamps on ET:				Number of Lamps on ET:					
					1	2	3	4	1	2	3	4		
OSRAM	ET-A 60/220-240	220-240, 50-60Hz	20-60W	ET	Green	Red	Green	Green	Green	Green	Green	Green	Green	Green
OSRAM	ET-LED 30/220-240	220-240, 50-60Hz	2-30W	ET	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green
OSRAM	ET-P 60/220-240 (Gen 2)	220-240, 50-60Hz	20-60W	ET	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green
OSRAM	ET-Parrot 105/220-240 I	220-240, 50-60Hz	35-105W	ET	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green
OSRAM	ET-Parrot 150/220-240 I	220-240, 50-60Hz	50-150W	ET	Green	Red	Red	Red	Yellow	Yellow	Yellow	Yellow	Yellow	Yellow
OSRAM	ET-Parrot 70/220-240 I	220-240, 50-60Hz	20-70W	ET	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green
OSRAM	ET-Redback 60/230-240	230-240, 50Hz	20-60W	ET	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green
OSRAM	ET-REDBACK 40VA/230-20	230-240, 50-60Hz	10-40W	ET	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green
OSRAM	ET-ZE 60/220-240	220-240, 50-60Hz	20-60W	ET	Red	Red	Red	Red	Green	Green	Green	Green	Green	Green
OSRAM	HALOTRNIC HTN75/230-240 I	230-240, 50-60Hz	20-75W	ET	Yellow	Red	Yellow	Yellow	Green	Green	Green	Green	Green	Green
OSRAM	HTB 105/220-240	220-240, 50-60Hz	35-105W	HT	Green	Green	Green	Green	Red	Yellow	Yellow	Yellow	Yellow	Yellow
OSRAM	HTB 70/220-240	220-240, 50-60Hz	20-70W	HT	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green
OSRAM	Hi DALI 105/230-240 DIM	230-240, 50-60Hz	35-105W	HTi										
OSRAM	HTL105/230-240	230-240, 50-60Hz	35-105W	HT	Red	Red	Red	Red	Green	Green	Green	Green	Green	Green
OSRAM	HTM 105/230-240	230-240, 50-60Hz	35-105W	HT	Green	Green	Green	Green	Yellow	Yellow	Yellow	Yellow	Yellow	Yellow
OSRAM	HTM 150/230-240	230-240, 50-60Hz	50-150W	HT	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green
OSRAM	HTM 70/230-240	230-240, 50-60Hz	20-70W	HT	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green
OSRAM	IZ-A50/240	240,50-60Hz	50W	ET	Green	Green	Green	Green	Yellow	Yellow	Yellow	Yellow	Yellow	Yellow
OSRAM	IZ-HALD50/220-240	220-240, 50-60Hz	20-50W	ET	Green	Green	Green	Green	Green	Green	Green	Green	Green	Green

OTHERs ETs

ET Compatibility traffic light system:

- Green very good compatibility (no problems with ET)
- Yellow good compatibility habits (partially flickering)
- Red partial critical compatibility habits (flickering or darker light may occur)
- White not tested

Lamp

Type	PIN G4 200 lm 1,7W	PIN G4 300 lm 2,4W
Product Picture		
EAN Product Code	4052899964358 AB44659	4052899964372 AB44660

ET					Number of Lamps on ET:				Number of Lamps on ET:			
Brand	Model	Voltage range	Power	Type	1	2	3	4	1	2	3	4
abi	SET210(50-210VA) A	220-240V, 50Hz	50-210VA	ET	Green	Green	Yellow	Yellow	Green	Green	Green	Green
Berker	Igel 20-105w 2921	230-240,50-60Hz	20-105W	ET	Red	Red	Red	Red	Red	Red	Red	Red
Berker	SNT 70/QU 2918	230,50-60Hz	20-70W	ET	Green	Green	Green	Green	Green	Green	Green	Green
Berker	SNTF II 35-105W 2927	230,50-60Hz	35-105W	ET	Green	Green	Green	Green	Yellow	Yellow	Green	Green
BLOCK	HES 105K	230-240,50-60Hz	35-105W	ET	Green	Green	Green	Green	Yellow	Yellow	Red	Red
BLOCK	HES 70K	230-240,50-60Hz	20-70W	ET	Red	Red	Red	Red	Red	Red	Red	Red
EVN	CLOU 60(T41/09)	230-240,50-60Hz	10-60W	ET	Red	Red	Red	Red	Red	Red	Red	Red
EVN	MINJOKER 70(T27/10)	\	70W	ET	Red	Red	Red	Red	Red	Red	Red	Red
EVN	TAB 70 (3310)	230,50-60Hz	20-70W	ET	Green	Green	Green	Green	Green	Green	Green	Green
FN LIGHT	TL105S 20-105W 461	230-240,50-60Hz	20-105W	ET	Green	Green	Green	Green	Green	Green	Green	Green
goodbay	SET110LV(35-110W)	220-240,50Hz	35-110W	ET	Green	Green	Green	Green	Green	Green	Green	Green
JUNG	SNT 105 F	230,50-60Hz	20-105W	ET	Green	Green	Green	Green	Green	Green	Green	Yellow
JUNG	SNT 70 F	230,50-60Hz	20-70W	ET	Green	Green	Green	Green	Green	Green	Green	Yellow
nobile	EN-60D2	230,50-60Hz	20-60W	ET	Red	Red	Red	Red	Green	Green	Green	Green
nobile	EN-80F	230,50-60Hz	20-80W	ET	Yellow	Green	Green	Green	Green	Green	Green	Green
OSRAM	HTL225	220-240,50-60Hz	50-225W	ET	Green	Yellow	Yellow	Green	Red	Red	Red	Red
OSRAM	OT15	220-240,50-60Hz	15W	OT	Green	Green	Green	Green	Green	Green	Green	Yellow
OSRAM	OT30	220-240,50-60Hz	30W	OT	Green	Green	Green	Green	Green	Green	Green	Green
OSRAM	OT60	220-240,50-60Hz	60W	OT	Green	Green	Green	Green	Green	Green	Green	Green
Paulmann	Disc electronic S 70	230,50-60Hz	20-70W	ET	Green	Green	Green	Green	Green	Green	Green	Green
Paulmann	Mipro 70	230,50-60Hz	20-70W	ET	Red	Red	Red	Red	Red	Red	Red	Green
Paulmann	Profi 80	220-240,50Hz	20-80W	ET	Yellow	Yellow	Green	Green	Yellow	Green	Green	Green
PHILIPS	Primaline 70 230-240	230-240,50-60Hz	20-70W	ET	Green	Green	Green	Green	Green	Green	Green	Green
SLV	461060	230,50-60Hz	10-60W	ET	Green	Green	Green	Green	Green	Green	Green	Green
TCI	PUMA 105	230-240,50-60Hz	20-105W	ET	Green	Green	Green	Green	Green	Green	Green	Green
TCI	ROUND 70	230,50-60Hz	20-70W	ET	Green	Green	Green	Green	Green	Green	Green	Green
TCI	SHARK60	220-240,50-60Hz	10-60W	ET	Red	Red	Red	Red	Green	Green	Yellow	Yellow

Please Note:

- The compatibility list is based upon testing conducted by the manufacturer in a lab simulated environment, and the results can vary in certain field applications due to a number of factors. OSRAM does not take over any responsibility, warranty or liability that this results can also achieved by using the devices under other conditions, or when using successor models of the tested devices, or different models of the same manufacturer, or when using other LED lamp types
- The absence of a dimmer from this chart does not necessarily imply incompatibility.
- Please reference the dimmer manufacturer's instructions for installation.
- LED lamps contain several electronic components. Under unfavourable conditions these can lead to acoustic noise. In case of resonance even low noise can cause audible effect. Possible factors influencing this are the installation, the design of the lamp holder and the luminaire (acoustic resonance effect) as well as the dimmer or the transformer (harmonics or electronic resonance).
- Subject to change without notice
- Errors and omission excepted
- Always make sure to use the most recent release

Application Notes:

- For best dimming results trailing edge dimmer type is recommended.
- Trailing edge type dimmer requires the neutral wire for installation.

Bitte beachten:

- Die Kompatibilitätsliste basiert auf Tests, die der Hersteller in einer im Labor simulierten Umgebung durchgeführt hat. Die Ergebnisse können aufgrund verschiedener Faktoren in manchen Praxisanwendungen abweichen. OSRAM übernimmt keinerlei Verantwortung, Garantie oder Haftung dafür, dass diese Ergebnisse tatsächlich mit den Geräten unter anderen Bedingungen, mit Nachfolgemodellen der getesteten Geräte, mit anderen Modellen desselben Herstellers oder bei Verwendung anderer LED-Lampentypen erreicht werden.
- Das Fehlen eines Dimmers in der Abbildung bedeutet nicht, dass ein Dimmer nicht kompatibel ist.
- Lesen Sie stets die Installationsanweisungen des Dimmerherstellers.
- LED-Lampen bestehen aus mehreren elektronischen Komponenten. Unter ungünstigen Bedingungen können diese Störgeräusche erzeugen. Im Resonanzfall können selbst geringe Geräusche einen hörbaren Effekt hervorrufen. Einflussfaktoren können die Installation, die Gestaltung des Lampenträgers, die Leuchte (akustischer Resonanzeffekt), der Dimmer oder der Trafo (Oberschwingungen oder elektronische Resonanz) sein.
- Änderungen vorbehalten.
- Irrtümer und Auslassungen vorbehalten.
- Vergewissern Sie sich, dass Sie stets die aktuellste Version benutzen.

Anwendungshinweis:

- Um bestmögliche Dimmergebnisse zu erzielen, wird die Verwendung von Phasenabschnitt-Dimmern empfohlen.
- Phasenabschnitt-Dimmer erfordern bei der Installation einen Neutralleiter.

LEDVANCE GmbH

Head Office:

Parkring 29-33
85748 Garching, Germany
Phone +49 89 780673-100
Fax +49 89 780673-XXX
www.ledvance.com