

## DIMMER COMPATIBILITY CL B

### BASIC INFORMATION:

#### 1. WHAT IS THE PRODUCT CODE AND WHERE DO I FIND IT?

The product code describes the lamp type. It contains 7 letters and digits and is starting with "A". Below an example for the product code of the stamp of the lamp:



220-240V **AC01770** 2700K  
 13 W 50/60 Hz 27 mA  
 Made in Germany XXX-XXXX

#### 2. HOW CAN I READ THE FOLLOWING CHARTS?

Legend:  
 Information about the dimmability of the lamps. Green means very good dimmability, yellow means limited dimmability, red means undesired dimmability etc.

List of dimmers tested in laboratory conditions

Legend					PARATHOM DIM CL P 25 Glass Frosted	PARATHOM DIM CL P 25 FIL	PARATHOM DIM CL P 40 Frosted	PARATHOM DIM CL P 40
Very good dimmability with indicated number of lamps (dimming range greater than 75%)								
Limited dimmability with indicated number of lamps (dimming range smaller than 75%)								
Undesired dimmability								
Not relevant								
Dimmer					Dimming	Dimming	Dimming	Dimming
Brand	Model	Voltage range	Power	Type	range 1 lamps	range 4 lamps	range 1 lamps	range 4 lamps
ABB	STD 50-3	230/50Hz	60-500	L	89-3%	100-5%	89-3%	100-5%
Altenburger	50_3	230/50Hz			100-3%	100-3%	100-3%	97-2%
AURORA	DSP 400	230/50Hz	400	R	100-3%	100-3%	96-0%	96-0%
Berker	2861	230/50Hz	50-420	U	96-10%	99-8%	96-10%	99-8%
bticino	NT4402N	230/50Hz	500	R	100-3%	96-4%	96-4%	85-2%
Bticino	NT4408HC/HD/HS4	230/50Hz			100-3%	100-3%	94-0%	96-0%
Bticino	L/N/NT4411N	230/50Hz			100-3%	100-3%	94-9%	96-3%
Busch-Jaeger	2250 U	230/50Hz	60-600	L	100-12%	100-3%	100-3%	97-16%
Busch-Jaeger	6513 U-102	230/50Hz	420	T	100-12%	100-3%	100-3%	96-13%
Busch-Jaeger	6526 U	230/50Hz			100-12%	100-12%	100-3%	99-16%
Busch-Jaeger	6523 U-102	230/50Hz	40-420	T	100-13%	100-13%	100-3%	97-10%
CENTURY CONTROL	MULTI DIMMER	230/50Hz	60-600	U	95-3%	99-3%	95-3%	99-3%
DINUY	RELEI LEI	230/50Hz	400	LED	100-3%	100-3%	100-3%	96-7%
ELKO	400GLI	230/50Hz			100-3%	93-3%	96-4%	96-4%
ELKO	315GLE	230/50Hz	20-	T	100-3%	100-3%	100-3%	100-2%
ELKO	600GLI	230/50Hz	40-600	U	100-3%	100-6%	100-3%	96-2%
ELKO	420GLE/I	230/50Hz	40-420	U	100-3%	101-3%	101-3%	99-2%

Information about the OSRAM lamp type

Assessment of the results into categories. Includes the number of lamps and the related dimming range

## DIMMER KOMPATIBILITÄT CL B

### BASISINFORMATIONEN:

#### 1. WAS IST DER PRODUKTCODE UND WO FINDE ICH IHN?

Der Produktcode beschreibt den Lampentyp. Er besteht aus sieben Buchstaben und Ziffern und beginnt mit einem "A". Nachfolgend ein Beispiel eines Produktcodes auf dem Aufdruck der Lampe.



220-240V **AC01770** 2700K  
13 W 50/60 Hz 27 mA  
Made in Germany XXX-XXXX

#### 2. WIE LESE ICH DIE FOLGENDEN TABELLEN?

Legende: Angaben zur Dimmbarkeit der Lampen. Grün bedeutet eine sehr gute Dimmbarkeit mit der angegebenen Lampenanzahl, gelb bedeutet eine eingeschränkte Dimmbarkeit, rot bedeutet, dass unerwünschtes dimmverhalten auftreten kann etc.

Liste der getesteten Dimmer

Legend					
Very good dimmability with indicated number of lamps (dimming range greater than 75%)					
Limited dimmability with indicated number of lamps (dimming range smaller than 75%)					
Undesired dimmability					
Not relevant					
Dimmer					
Brand	Model	Voltage range	Power	Type	
ABB	STD 50-3	230/50Hz	60-500	L	
Altenburger	50_3	230/50Hz	400	R	
AURORA	DSP 400	230/50Hz	400	R	
Berker	2861	230/50Hz	50-420	U	
bticino	NT4402N	230/50Hz	500	R	
bticino	NT4408HC/HD/HS4r	230/50Hz	420	T	
bticino	L/N/NT4411N	230/50Hz	420	T	
Busch-Jaeger	2250 U	230/50Hz	60-600	L	
Busch-Jaeger	6513 U-102	230/50Hz	420	T	
Busch-Jaeger	6526 U	230/50Hz	420	T	
Busch-Jaeger	6523 U-102	230/50Hz	40-420	T	
CENTURY CONTROL	MULTI DIMMER	230/50Hz	60-600	U	
DINUVY	RE EL1 LE1	230/50Hz	400	LED	
ELKO	400GLI	230/50Hz	40-420	U	
ELKO	315GLE	230/50Hz	20-	T	
ELKO	600GLI	230/50Hz	40-600	U	
ELKO	420GLE/1	230/50Hz	40-420	U	















  

PARATHOM DIM CL P 25 Glass Frosted		PARATHOM DIM CL P 25 FIL		PARATHOM DIM CL P 40 Frosted		PARATHOM DIM CL P 40	
Lampo	Lamos	Lampo	Lamos	Lampo	Lamos	Lampo	Lamos
058075101319 / AC08257	058075101333 / AC08258	40580751081955 / AC08255	4058075147935 / AC08399	4058075101418 / AC08259	4058075101385 / AC08317	4058075101432 / AC08318	
Dimming	Dimming	Dimming	Dimming	Dimming	Dimming	Dimming	Dimming
range 1	range 4	range 1	range 4	range 1	range 4	range 1	range 4
89-3%	100-5%	89-3%	100-5%	96-0%	96-0%	88-2%	99-5%
100-3%	100-3%	100-3%	100-3%	96-0%	96-0%	97-2%	97-2%
96-10%	99-8%	96-10%	99-8%	96-4%	96-4%	100-1%	99-9%
100-3%	100-3%	100-3%	100-3%	94-0%	96-0%	85-2%	85-2%
100-3%	100-3%	100-3%	100-3%	94-9%	96-3%	97-1%	97-1%
40-3%		40-3%				97-8%	97-1%
100-3%	100-3%	100-3%	100-3%			96-13%	99-15%
100-12%	100-3%	100-12%	100-3%		96-6%	97-10%	97-10%
100-3%	100-13%					96-1%	100-2%
95-3%	99-3%	95-3%	99-3%			85-2%	85-2%
100-3%	100-3%	100-3%	100-3%	96-4%	96-4%	100-1%	100-2%
	93-3%		93-3%			85-2%	85-2%
	100-3%		100-3%			96-2%	96-2%
100-3%	100-6%	100-3%	100-6%			99-2%	100-2%
	101-3%		101-3%	94-6%	94-6%	97-2%	97-2%










Angaben zum OSRAM Lampentyp

Bewertung der Testergebnisse in Ampel Kategorien. Beinhaltet sowohl die Lampenanzahl als auch den dimmbaren Bereich










## DIMMER COMPATIBILITY CL B

Legend					SUPERSTAR CL B 25		SUPERSTAR CL B 40		SUPERSTAR CL B / BA 40		SUPERSTAR CL B / BA 40		SUPERSTAR CL B 60			
	Very good dimmability with indicated number of lamps (dimming range greater than 75%)															
	Limited dimmability with indicated number of lamps (dimming range smaller than 75%)				EAN / Basic Code		EAN / Basic Code		EAN / Basic Code		EAN / Basic Code		EAN / Basic Code			
	Undesired dimmability				4058075107502 / AC08160 4058075051867 / AC08161 4058075054363 / AC08161		4052899904415 / AC08387 4058075127951 / AC08387		4052899961814 / AC08162 4058075808874 / AC08165 4052899959163 / AC08166 4058075054264 / AC08166 4058075808744 / AC08180 4058075108042 / AC08181		4058075107847 / AC08163 4058075107663 / AC08164 4058075107885 / AC08167 4058075107649 / AC08168 4058075808744 / AC08180 4058075808737 / AC08182		4058075811393 / AC10264 4058075107786 / AC10267			
	Not relevant				Dimming range 1 Lamp		Dimming range 4 Lamps		Dimming range 1 Lamp		Dimming range 4 Lamps		Dimming range 1 Lamp		Dimming range 4 Lamps	
Brand	Model	Voltage range	Power	Type	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps		
ABB	STD 50-3	230/50Hz	60-500	L	88-3%	100-5%	100-36%	100-40%	88-2%	99-5%	88-2%	99-5%	100-11%			
Altenburger	50,3	230/50Hz			100-3%	100-3%			97-2%	97-2%	97-2%	97-2%	100-25%	100-22%		
AURORA	DSP 400	230/50Hz	400	R		100-3%	99-0%	99-0%					100-0%	100-0%		
Berker	2861	230/50Hz	50-420	U	97-10%	99-8%		100-48%	100-11%	99-9%	100-11%	99-9%				
Bticino	L/N/NT4411N	230/50Hz			100-3%	100-3%	99-7%	99-4%	94-1%	97-2%	94-1%	97-2%	88-5%	89-5%		
Bticino	L/N/NT4408	230/50Hz			100-3%	100-3%		100-0%	95-1%	97-1%	95-1%	97-1%	100-0%	100-0%		
Biticino	NT4402N	230/50Hz	500	R		96-4%		99-27%								
Busch-Jaeger	6513 U-102	230/50Hz	420	T		100-3%	100-43%	100-31%	97-16%	97-1%	97-16%	97-1%		100-17%		
Busch-Jaeger	6523 U-102	230/50Hz	40-420	T		100-13%	99-7%	99-5%		97-10%		97-10%	96-20%	97-21%		
Busch-Jaeger	2250 U	230/50Hz	60-600	L			100-25%	100-27%					100-8%			
Busch-Jaeger	6526 U	230/50Hz			100-12%	100-3%	99-48%		96-13%	99-15%	96-13%	99-15%	100-29%	100-29%		
CENTURY CONTROL	MULTI DIMMER	230/50Hz	60-600	U	95-3%	99-3%	100-12%	100-16%		96-1%		96-1%	100-0%	100-0%		
DINUY	RE EL1 LE1	230/50Hz	400	LED	100-3%	100-3%	100-2%	100-1%	100-1%	100-2%	100-1%	100-2%	100-3%	100-3%		
ELKO	400GLI	230/50Hz				93-3%				91-2%		91-2%				
ELKO	315GLE	230/50Hz	20-315	T		100-3%		100-39%		96-2%		96-2%		100-18%		
ELKO	600GLE/I	230/50Hz				100-3%	99-0%	100-0%	99-2%	100-2%	99-2%	100-2%	98-0%	99-0%		
ELKO	600GLI	230/50Hz	40-600	U	100-3%	100-6%	100-33%	100-35%	86-2%	98-3%	86-2%	98-3%	100-17%	100-19%		
ELKO	420GLE/I	230/50Hz	40-420	U		100-3%	100-5%	99-5%	71-5%	97-2%	71-5%	97-2%	100-5%	100-5%		
ELKO	1000LRI	230/50Hz			99-3%	100-3%	100-0%	100-0%	94-1%	96-2%	94-1%	96-2%	100-0%	100-0%		
ELKO	630GLE	230/50Hz	20-630	U	82-3%	100-3%		100-20%	93-2%	100-2%	93-2%	100-2%	100-15%	100-12%		
Eltako	EUD61NPN-UC	230/50Hz	5-400	R / L / C	100-3%	100-3%	100-1%	99-1%	100-1%	100-2%	100-1%	100-2%	99-1%	99-1%		
Feller	40200.LEDxxx	230/50Hz			99-3%	100-3%	100-39%	100-36%	98-2%	100-1%	98-2%	100-1%	100-21%	100-18%		
Feller	40600.RLC	230/50Hz	20-600	U		100-3%	99-0%	100-0%	99-2%	100-2%	99-2%	100-2%	98-0%	99-0%		
Feller	40600.RC	230/50Hz			82-3%	100-3%		100-20%	93-2%	100-2%	93-2%	100-2%	100-15%	100-12%		
Feller	40600.RL	230/50Hz			100-3%	100-6%	100-33%	100-35%	86-2%	98-3%	86-2%	98-3%	100-17%	100-19%		
Feller	40420.RLC	230/50Hz				100-3%	100-5%	99-5%	71-5%	97-2%	71-5%	97-2%	100-5%	100-5%		
Feller	31000	230/50Hz			99-3%	100-3%	100-0%	100-0%	94-1%	96-2%	94-1%	96-2%	100-0%	100-0%		
GIRA	226200	230/50Hz			93-3%	100-3%	100-7%	100-0%	88-2%	97-1%	88-2%	97-1%	100-1%	100-0%		
Gira	030700	230/50Hz	20-525	T	100-3%	100-3%	100-36%	99-31%	97-4%	96-2%	97-4%	96-2%	100-18%	100-15%		
Gira	117600	230/50Hz	50-420	U		100-8%		100-48%	99-11%	100-8%	99-11%	100-8%				
Gira	238500	230/50Hz			84-3%	100-3%	99-16%	98-14%	96-1%	98-1%	96-1%	98-1%	100-12%	100-12%		

## DIMMER COMPATIBILITY CL B

Legend					SUPERSTAR CL B 25		SUPERSTAR CL B 40		SUPERSTAR CL B / BA 40		SUPERSTAR CL B / BA 40		SUPERSTAR CL B 60	
	Very good dimmability with indicated number of lamps (dimming range greater than 75%)													
	Limited dimmability with indicated number of lamps (dimming range smaller than 75%)				EAN / Basic Code		EAN / Basic Code		EAN / Basic Code		EAN / Basic Code		EAN / Basic Code	
	Undesired dimmability													
	Not relevant													
					4058075107502 / AC08160 4058075051867 / AC08161 4058075054363 / AC08161		4052899904415 / AC08387 4058075127951 / AC08387		4052899961814 / AC08162 4058075808874 / AC08165 4052899959163 / AC08166 4058075054264 / AC08166 4058075808744 / AC08180 4058075108042 / AC08181		4058075107847 / AC08163 4058075107663 / AC08164 4058075107885 / AC08167 4058075107649 / AC08168 4058075808744 / AC08180 4058075808737 / AC08182		4058075811393 / AC10264 4058075107786 / AC10267	
Dimmer					Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps
Brand	Model	Voltage range	Power	Type										
Gira	217400	230/50Hz	4X20-250	KNX-U	99-3%	100-3%	100-3%	100-3%	100-2%	100-2%	100-2%	100-2%	100-17%	100-13%
Hager	WUD87	230/50Hz	400	LED-U	100-3%	100-3%	100-29%	99-28%	96-2%	99-2%	96-2%	99-2%	100-21%	100-20%
Hamilton	KP1X40	230/50Hz	400										95-19%	
Hugo Müller	paladin 872110 led	230/50Hz			100-3%	100-3%	100-2%	100-1%	100-1%	100-2%	100-1%	100-2%	100-3%	100-3%
Jung	225 NVDE	230/50Hz	20-500	L	93-3%	100-3%	100-7%	100-0%	88-2%	97-1%	88-2%	97-1%	100-1%	100-0%
Jung	225 TDE	230/50Hz			100-3%	100-3%	100-36%	99-31%	97-4%	96-2%	97-4%	96-2%	100-18%	100-15%
Jung	254 UDIE1	230/50Hz			100-10%	100-8%		100-48%	99-11%	100-8%	99-11%	100-8%		
Jung	1224 LEDUDE	230/50Hz		LED	84-3%	100-3%	99-16%	98-14%	96-1%	98-1%	96-1%	98-1%	100-12%	100-12%
Jung	3904 REGHE	230/50Hz			99-3%	100-3%	100-24%	100-29%	100-2%	100-2%	100-2%	100-2%	100-17%	100-13%
Legrand	665114	230/50Hz	400	U	100-3%	100-3%	99-7%	99-4%	94-1%	97-2%	94-1%	97-2%	88-5%	89-5%
Legrand	067083=048869=048	230/50Hz			100-3%	100-3%	99-7%	99-4%	94-1%	97-2%	94-1%	97-2%	88-5%	89-5%
Legrand	770061	230/50Hz	400	RL	97-3%	99-3%		100-18%		99-2%		99-2%	100-0%	100-0%
Legrand	099314	230/50Hz	300	RL		100-3%	100-0%	100-0%					100-0%	100-0%
Legrand	770062	230/50Hz	400	RLC		99-3%	100-0%	100-0%		99-2%		99-2%	100-0%	100-0%
Legrand	078405	230/50Hz	600	RLC	100-3%	100-3%		100-0%	95-1%	97-1%	95-1%	97-1%	100-0%	100-0%
MASTER	DM-DGL	230/50Hz	1000	U / LED	97-3%	100-3%	100-6%	100-1%	96-1%	100-2%	96-1%	100-2%	100-3%	100-1%
MASTER	DM-2500	230/50Hz	2500	U / LED	97-3%	100-3%	100-1%	98-1%	96-1%	99-2%	96-1%	99-2%		100-1%
Merten	MEG5136-0000	230/50Hz				100-3%		100-39%		96-2%		96-2%		100-18%
Merten	MEG5134-0000	230/50Hz			99-3%	100-3%	100-39%	100-36%	98-2%	100-1%	98-2%	100-1%	100-21%	100-18%
Merten	MEG5139-0000	230/50Hz				100-3%	99-0%	100-0%	99-2%	100-2%	99-2%	100-2%	98-0%	99-0%
Merten	MEG5137-0000	230/50Hz			82-3%	100-3%		100-20%	93-2%	100-2%	93-2%	100-2%	100-15%	100-12%
Merten	MEG5133-0000	230/50Hz			100-3%	100-6%	100-33%	100-35%	86-2%	98-3%	86-2%	98-3%	100-17%	100-19%
Merten	MEG5138-0000	230/50Hz				100-3%	100-5%	99-5%	71-5%	97-2%	71-5%	97-2%	100-5%	100-5%
Merten	MEG 5170-0300	230/50Hz	10-200	U	100-3%	100-3%	98-48%		97-3%	97-2%	97-3%	97-2%		
Merten	MEG 5131	230/50Hz	40-400	L	99-3%	100-3%	100-0%	100-0%	86-2%	98-1%	86-2%	98-1%	100-0%	100-0%
Merten	MEG 5132	230/50Hz			99-3%	100-3%	100-0%	100-0%	86-2%	98-1%	86-2%	98-1%	100-0%	100-0%
Merten	MEG 5140	230/50Hz	9-100	L	72-3%	100-3%	100-1%	100-0%	79-2%	99-2%	79-2%	99-2%	99-0%	100-0%
Merten	MEG 5135	230/50Hz	60-1000	L	99-3%	100-3%	100-0%	100-0%	94-1%	96-2%	94-1%	96-2%	100-0%	100-0%
MK	K4501	230/50Hz	180	L			100-18%	100-19%	76-2%	97-1%	76-2%	97-1%	90-10%	92-12%
NEXUS	881P-01	230/50Hz	400	L			100-0%	100-0%		94-1%		94-1%		

## DIMMER COMPATIBILITY CL B

Legend					SUPERSTAR CL B 25		SUPERSTAR CL B 40		SUPERSTAR CL B / BA 40		SUPERSTAR CL B / BA 40		SUPERSTAR CL B 60	
	Very good dimmability with indicated number of lamps (dimming range greater than 75%)													
	Limited dimmability with indicated number of lamps (dimming range smaller than 75%)				EAN / Basic Code		EAN / Basic Code		EAN / Basic Code		EAN / Basic Code		EAN / Basic Code	
	Undesired dimmability													
	Not relevant													
					4058075107502 / AC08160 4058075051867 / AC08161 4058075054363 / AC08161		4052899904415 / AC08387 4058075127951 / AC08387		4052899961814 / AC08162 4058075808874 / AC08165 4052899959163 / AC08166 4058075054264 / AC08166 4058075808744 / AC08180 4058075108042 / AC08181		4058075107847 / AC08163 4058075107663 / AC08164 4058075107885 / AC08167 4058075107649 / AC08168 4058075808744 / AC08180 4058075808737 / AC08182		4058075811393 / AC10264 4058075107786 / AC10267	
Dimmer					Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps
Brand	Model	Voltage range	Power	Type										
NIKO	310-01900	230/50Hz	5-200	U	100-3%	100-3%	100-3%	100-16%	100-1%	100-2%	100-1%	100-2%		
NIKO	330-00700	230/50Hz	5-200	U	100-3%	100-3%	100-12%	100-12%	100-1%	100-2%	100-1%	100-2%	100-10%	100-11%
Odace	S520512	230/50Hz			99-3%	100-3%	100-39%	100-36%	98-2%	100-1%	98-2%	100-1%	100-21%	100-18%
Odace	S520511	230/50Hz			100-3%	100-6%	100-33%	100-35%	86-2%	98-3%	86-2%	98-3%	100-17%	100-19%
Odace	S520515	230/50Hz				100-3%	100-5%	99-5%	71-5%	97-2%	71-5%	97-2%	100-5%	100-5%
Odace	S520518	230/50Hz			72-3%	100-3%	100-1%	100-0%	79-2%	99-2%	79-2%	99-2%	99-0%	100-0%
Osram	HTI DALI 315 DIM	230/50Hz	20-315	DALI-T	100-3%	100-3%	100-27%	100-25%	96-1%	96-1%	96-1%	96-1%	100-12%	100-11%
PEHA	435 HAN	230/50Hz	60-600	L		100-6%	100-37%	99-41%		99-2%		99-2%	100-23%	
Schneider	400GLI	230/50Hz	40-400	T		93-3%				91-2%		91-2%		
Schneider	SBD315RC	230/50Hz				100-3%		100-39%		96-2%		96-2%		100-18%
Schneider	SBD200LED	230/50Hz	400		99-3%	100-3%	100-39%	100-36%	98-2%	100-1%	98-2%	100-1%	100-21%	100-18%
Schneider	SBD600RCRL	230/50Hz				100-3%	99-0%	100-0%	99-2%	100-2%	99-2%	100-2%	98-0%	99-0%
Schneider	SBD630RC	230/50Hz			82-3%	100-3%		100-20%	93-2%	100-2%	93-2%	100-2%	100-15%	100-12%
Schneider	SBD600RL	230/50Hz			100-3%	100-6%	100-33%	100-35%	86-2%	98-3%	86-2%	98-3%	100-17%	100-19%
Schneider	SBD420RCRL	230/50Hz				100-3%	100-5%	99-5%	71-5%	97-2%	71-5%	97-2%	100-5%	100-5%
Schneider	5170	230/50Hz			100-3%	100-3%	98-48%		97-3%	97-2%	97-3%	97-2%		
Schneider	SBD400RL	230/50Hz			99-3%	100-3%	100-0%	100-0%	86-2%	98-1%	86-2%	98-1%	100-0%	100-0%
Schneider	SBDSP1	230/50Hz			72-3%	100-3%	100-1%	100-0%	79-2%	99-2%	79-2%	99-2%	99-0%	100-0%
Schneider	ATTD1000RL	230/50Hz			99-3%	100-3%	100-0%	100-0%	94-1%	96-2%	94-1%	96-2%	100-0%	100-0%
Shuttle	SDIM-T-LED-500W	230/50Hz	2-500	T & LED-T	100-3%	100-3%	99-22%	100-20%	96-1%	96-1%	96-1%	96-1%	100-10%	100-13%
Siemens	5TC8 284	230/50Hz	20-525	T			99-22%	99-4%						99-10%
Siemens	5WG1-528-1AB31	230/50Hz	20-500	KNX-U	100-3%	100-3%	100-2%	100-0%	99-2%	98-2%	99-2%	98-2%	100-0%	100-0%
VADSBO	LD 220	230/50Hz	1-200	U	97-3%	100-3%	100-18%	99-4%	96-1%	96-2%	96-1%	96-2%	100-31%	100-2%
VARILIGHT	HQ3W	230/50Hz	400			97-8%	98-37%	98-37%		96-8%		96-8%	100-5%	
VARILIGHT	JQP401W	230/50Hz	400	T			100-13%	100-14%					100-0%	
Vimar	20135	230/50Hz	3 - 100	U	100-3%	100-3%	100-12%	100-12%	100-1%	100-2%	100-1%	100-2%	100-7%	100-6%
ZANO	WH401	230/50Hz	400	L		98-3%	100-0%	100-0%		99-2%		99-2%	100-0%	
ZANO	WH251	230/50Hz	250				100-0%	100-0%		36-1%		36-1%		
ZANO	Z GRID 700	230/50Hz	250	LED	97-3%	97-3%	100-1%	100-0%	96-1%	98-1%	96-1%	98-1%		
ZANO	Z GRID 500	230/50Hz	500			99-3%	100-0%	100-0%	84-2%	97-1%	84-2%	97-1%		

**Please Note:**

- The compatibility list is based upon testing conducted by the manufacturer in a lab simulated environment, and the results can vary in certain field applications due to a number of factors. OSRAM does not take over any responsibility, warranty or liability that this results can also achieved by using the devices under other conditions, or when using successor models of the tested devices, or different models of the same manufacturer, or when using other LED lamp types
- The absence of a dimmer from this chart does not necessarily imply incompatibility.
- Please reference the dimmer manufacturer's instructions for installation.
- LED lamps contain several electronic components. Under unfavourable conditions these can lead to acoustic noise. In case of resonance even low noise can cause audible effect. Possible factors influencing this are the installation, the design of the lamp holder and the luminaire (acoustic resonance effect) as well as the dimmer or the transformer (harmonics or electronic resonance).
- Subject to change without notice
- Errors and omission excepted
- Always make sure to use the most recent release

**Application Notes:**

- For best dimming results trailing edge dimmer type is recommended.
- Trailing edge type dimmer requires the neutral wire for installation.

**Bitte beachten:**

- Die Kompatibilitätsliste basiert auf Tests, die der Hersteller in einer im Labor simulierten Umgebung durchgeführt hat. Die Ergebnisse können aufgrund verschiedener Faktoren in manchen Praxisanwendungen abweichen. OSRAM übernimmt keinerlei Verantwortung, Garantie oder Haftung dafür, dass diese Ergebnisse tatsächlich mit den Geräten unter anderen Bedingungen, mit Nachfolgemodellen der getesteten Geräte, mit anderen Modellen desselben Herstellers oder bei Verwendung anderer LED-Lampentypen erreicht werden.
- Das Fehlen eines Dimmers in der Abbildung bedeutet nicht, dass ein Dimmer nicht kompatibel ist.
- Lesen Sie stets die Installationsanweisungen des Dimmerherstellers.
- LED-Lampen bestehen aus mehreren elektronischen Komponenten. Unter ungünstigen Bedingungen können diese Störgeräusche erzeugen. Im Resonanzfall können selbst geringe Geräusche einen hörbaren Effekt hervorrufen. Einflussfaktoren können die Installation, die Gestaltung des Lampenträgers, die Leuchte (akustischer Resonanzeffekt), der Dimmer oder der Trafo (Oberschwingungen oder elektronische Resonanz) sein.
- Änderungen vorbehalten.
- Irrtümer und Auslassungen vorbehalten.
- Vergewissern Sie sich, dass Sie stets die aktuellste Version benutzen.

**Anwendungshinweis:**

- Um bestmögliche Dimmergebnisse zu erzielen, wird die Verwendung von Phasenabschnitt-Dimmern empfohlen.
- Phasenabschnitt-Dimmer erfordern bei der Installation einen Neutralleiter.

**LEDVANCE GmbH**

Head Office:

Parkring 29-33  
85748 Garching, Germany  
Phone +49 89 780673-100  
Fax +49 89 780673-XXX  
[www.ledvance.com](http://www.ledvance.com)