

PRODUCT DATASHEET

P CLAS A 100 13 W/2700K E27

PARATHOM CLASSIC A DIM | Dimmable LED lamps, classic bulb shape



AREAS OF APPLICATION

- Domestic applications
- General illumination
- Outdoor use in outdoor luminaires only (minimum IP65)

PRODUCT BENEFITS

- Low energy consumption
- High color consistency thanks to narrow binning
- Easy replacement of classic lamps thanks to compact design

PRODUCT FEATURES

- Professional LED lamps for line voltage
- Dimmable (with many common dimmers, see also www.ledvance.com/dim)
- Long lifetime: up to 25,000 h
- Good quality of light; color rendering index $R_a \geq 80$; constant chromaticity



TECHNICAL DATA

Electrical data

Rated wattage	13.00 W
Nominal wattage	13.00 W
Nominal voltage	220...240 V
Max. lamp no. on circuit break. 10 A (B)	70
Max. lamp no. on circuit break. 16 A (B)	120
Operating frequency	50...60 Hz
Power factor λ	> 0.90
Claimed equiv. conventional lamp power	100 W


Photometrical data

Nominal luminous flux	1521 lm
Rated luminous flux	1521 lm
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	2700 K
Luminous flux	1521 lm
Color rendering index Ra	≥ 80
Standard deviation of color matching	≤ 6 sdc _m
Rated color temperature	2700 K
Color rendering index Ra	≥ 80

Light technical data

Warm-up time (60 %)	< 1.00 s
Starting time	< 0.5 s

Dimensions & weight



Overall length	120.0 mm
----------------	----------

Diameter	60.0 mm
Outer bulb	A60
Length	120.0 mm

Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
Maximum temperature at tc test point	98 °C

Lifespan

Nominal lamp life time	25000 h
Rated lamp life time	25000 h
Number of switching cycles	100000
Lumen maintenance at end of service life	0.70

Additional product data

Base (standard designation)	E27
Mercury content	0.0 mg
Mercury-free	Yes
Design / version	frosted
Show WEEE picto	Yes
Product remark	All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value/LED lamps contain several electronic components. Under unfavourable conditions these can lead to acoustic noise. In case of resonance even low noise can cause audible effect. Possible factors influencing this are the installation, the design of the lamp holder and the luminaire (acoustic resonance effect) as well as the dimmer or the transformer (harmonics or electronic resonance)

Capabilities

Dimmable	Yes
-----------------	-----

Certificates & standards

Energy efficiency class	A+
Energy consumption	14 kWh/1000h

Country-specific categorizations

Order reference	LEDPLA100D 13W
------------------------	----------------

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075292598	Folding carton box 1	61 mm x 61 mm x 120 mm	123.00 g	0.45 dm ³
4058075292604	Shipping carton box 10	348 mm x 145 mm x 159 mm	1477.00 g	8.02 dm ³
4058075462618	Folding carton box 1	61 mm x 61 mm x 120 mm	87.00 g	0.45 dm ³
4058075462625	Shipping carton box 10	318 mm x 133 mm x 134 mm	968.00 g	5.67 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

REFERENCES / LINKS

For dimming conformity see

▶ www.ledvance.com/dim

For further products and actual information concerning LED lamps see

▶ www.ledvance.com/ledlamps

For Guarantee see

▶ www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.