



CERTIFICATE

No. U6 097386 0049 Rev. 00

Holder of Certificate: LEDVANCE GmbH

Parkring 29-33
85748 Garching
GERMANY

Certification Mark:



Product:

**Power supplies
(LED POWER SUPPLY)**

The product was voluntarily tested according to the listed standards. The product can be marked with the certification mark shown above. The certification mark must not be altered in any way. See also notes overleaf.

Test report no.:

64142205000801

Date,

2020-06-04

(Taylor Yao)

CERTIFICATE

No. U6 097386 0049 Rev. 00

Model(s): DR DALI-PFM-26/220-240/700;
DR DALI-PFM-44/220-240/1050;
DR DALI-PFM-60/220-240/1A4;
LVED SUP 60/220-240/1A4 DIM;
DR DALI-SUP-45/220-240/24;
LVED SUP 45/220-240/24 DIM;
DR DALI-SUP-80/220-240/24;
LVED SUP 80/220-240/24 DIM;
DR DALI-SUP-150/220-240/24;
LVED SUP 150/220-240/24 DIM

Brand Name: LEDVANCE



Parameters:

Rated Input Voltage: See below table for details

Rated Frequency: See below table for details

Rated Input Current: See below table for details

Rated Output: See below table for details

Protection against Electric Shock: Class II (for independent type); SELV

Degree of Protection: IP20 (for independent type)

Method of Installation: See below table for details

Type of Output: See below table for details

ta: See below table for details

tc: See below table for details

CERTIFICATE

No. U6 097386 0049 Rev. 00

ZERTIFIKAT ◆ CERTIFICATE ◆ 認證證書 ◆ CERTIFICADO ◆ CERTIFIKAT ◆ CERTIFICAT

Model No.	Rated Input Voltage (V)/Rated Frequency (Hz)	Rated Input Current (A) Max.	Output Voltage (VDC)	Irated (mA)	Uout (VDC)	Prated (W)	Value Of ta; tc (°C)	Type of Output	Method of Installation	
DR DALI-PFM-26/220-240/700	220-240VAC; 50/60Hz; 196-245VDC	0.176 (AC); 0.15 (DC)	9-52	150	60	7.8	ta: 50; tc: 85	Constant Current Type	Independent (with endcap); Built-in (without endcap)	
				200		10.4				
				250		13				
				300		15.6				
				350		18.2				
				400		20.8				
				450		23.4				
				500		26				
				9-47.5		550				26.1
				9-43.5		600				26.1
				9-40		650				26
				9-37.5		700				26.3
DR DALI-PFM-44/220-240/1050	220-240VAC; 50/60Hz; 196-245VDC	0.275 (AC); 0.24 (DC)	9-52	700	60	36.4	ta: 50; tc: 90	Constant Current Type	Independent (with endcap); Built-in (without endcap)	
				750		39				
				800		41.6				
				850		41.7				
				900		44.1				
				9-46		950				43.7
				9-44		1000				44
				9-42		1050				44.1
DR DALI-PFM-60/220-240/1A4; LVED SUP 60/220-240/1A4 DIM	220-240VAC; 50/60Hz; 196-245VDC	0.385 (AC); 0.32 (DC)	9-52	700	60	36.4	ta: 50; tc: 90	Constant Current Type	Independent (with endcap); Built-in (without endcap)	
				750		39				
				800		41.6				
				850		44.2				
				900		46.8				
				950		49.4				
				1000		52				
				1050		54.6				
				1100		57.2				
				1150		59.8				
				9-50		1200				60
				9-48		1250				60
				9-46		1300				59.8
				9-44		1350				59.4
				9-43		1400				60.2

CERTIFICATE

No. U6 097386 0049 Rev. 00

Model No.	Rated Input Voltage (V)/Rated Frequency (Hz)	Rated Input Current (A) Max.	Urated (VDC)	Output Current (A)	Prated (W)	Value of ta; tc (°C)	Type of Output	Method of Installation
DR DALI-SUP-45/220-240/24; LVED SUP 45/220-240/24 DIM	220-240VAC; 50/60Hz	0.275	24	1.88	45	ta: 50; tc: 85	Constant Voltage Type	Independent
DR DALI-SUP-80/220-240/24; LVED SUP 80/220-240/24 DIM		0.462	24	3.33	80	ta: 45; tc: 85		
DR DALI-SUP-150/220-240/24; LVED SUP 150/220-240/24 DIM		0.825	24	6.25	150	ta: 45; tc: 85		

Tested according to:

EN 61347-2-13:2014/A1:2017
 EN 61347-1:2015
 EN 62384:2006/A1:2009

Production Facility(ies):

059266