


# OSRAM DALI magic

## Analysis- and commissioning tool for DALI installations

Please observe the safety precautions in handling the device



Operation and connection of the device only by electrically skilled persons



Indoor operation only

### General information

#### Application

PC independent:

- Control device for switching and dimming DALI lighting systems for testing of single lights or whole illumination equipments

Only in connection with PC and software:

- Standard interface DALI ↔ USB;
  - o Central control, analysis and programming of DALI systems (e. g. reading and writing of DALI device configurations) by means of software „DALI wizard“
  - o „DALI-Spy“- Functionality for recording data flow on the DALI line by means of software „DALI wizard“
  - o Programming of OSRAM ECG with 3DIM functionality by means of software „3DIM Tool“

#### Technical Data

- Power supply via USB: 5 V, 60 – 350 mA, integrated overvoltage protection
- External power supply: 6 V, 1 A, Reverse polarity protected
- External supply plug: DC, EIAJ-03
- USB connection: Type B acc. IEC 61076-3-108

#### Temperature and lifetime

- Work ambient temperature: 0 °C...+50 °C
- Storage temperature: -20 °C...+100 °C

#### Housing

- Dimensions: 120 mm x 79 mm x 28 mm (W x L x H)
- Housing material: ABS
- Protection class IP20
- Weight: 143 g



**DALI wizard and 3DIM Tool: Software download and manual at:**

[www.osram.com/lms-magic](http://www.osram.com/lms-magic)

#### Manufacturer address:

#### OSRAM GmbH

Steinerne Furt 62  
D-86167 Augsburg  
Germany

[www.osram.com](http://www.osram.com)

#### Technical support:

[www.osram.de](http://www.osram.de)  
[www.osram.com](http://www.osram.com)  
Customer Service Center Germany  
**+49 (0)89-6213-60 00**

# OSRAM

