

# PRODUCT DATASHEET

## DR-VAL -60/220-240/1A4

**LED DRIVER VALUE | Constant current LED driver with dedicated current**



---

### AREAS OF APPLICATION

- Suitable for LED luminaires and LED modules
- Applicable for luminaires of protection classes I and II
- For indoor SELV installations
- Offices, shopping centers, hospitals, restaurants, hotels

---

### PRODUCT BENEFITS

- Suitable for operation with many discrete LED and COB LED
- Excellent price/performance ratio
- 3 years guarantee
- Quick and simple installation
- High efficiency and reliability

---

### PRODUCT FEATURES

- Available in 15 W, 20 W, 30 W, 45 W and 60 W
- Integrated cable clamp for independent installation
- Lifetime: up to 35,000 h (at max. tc temperature)
- Type of protection: IP20
- Dedicated, constant output current
- Low ripple current < 5%
- Supply voltage: 220...240 V
- Operating frequency: 50/60 Hz
- Operated with less than 60 V: Safety extra-low voltage (SELV)
- Short-circuit and overload protection

**TECHNICAL DATA**

Electrical data

<b>Nominal voltage</b>	220...240 V
<b>Mains frequency</b>	50/60 Hz
<b>Input voltage AC</b>	198...264 V <sup>1)</sup>
<b>Total harmonic distortion</b>	17 % <sup>2)</sup>
<b>Power factor λ</b>	0.90 <sup>3)</sup>
<b>ECG efficiency</b>	87 % <sup>4)</sup>
<b>Device power loss</b>	7.8 W <sup>5)</sup>
<b>Protective conductor current</b>	0.4 mA
<b>Inrush current</b>	35 A <sup>6)</sup>
<b>Max. ECG no. on circuit breaker 10 A (B)</b>	12
<b>Max. ECG no. on circuit breaker 16 A (B)</b>	20
<b>Max. ECG no. on circuit breaker 25 A (B)</b>	31
<b>Surge capability (L-N)</b>	1 kV
<b>Nominal output voltage</b>	26...43 V <sup>7)</sup>
<b>U-OUT (working voltage)</b>	60 V
<b>Nominal output current</b>	1400 mA <sup>8)</sup>
<b>Output current tolerance</b>	±5 %
<b>Output ripple current (100 Hz)</b>	< 5 %
<b>Nominal output power</b>	60 W <sup>9)</sup>
<b>Galvanic isolation</b>	SELV
<b>Galvanic isolation primary/secondary</b>	3.75 kV

<sup>1)</sup> Permitted voltage range

<sup>2)</sup> At full load, 220...240 V, 50 Hz

<sup>3)</sup> Full load at 230 V

<sup>4)</sup> At full load and 230 V

<sup>5)</sup> At maximum LED load of 61 W


<sup>6)</sup>  $t_{width} = 250 \mu s$  (measured at 50 %  $I_{peak}$ )

<sup>7)</sup> Maximum 60 V

<sup>8)</sup> ±10%

<sup>9)</sup> Partial load 36...60 W

Dimensions & weight



<b>Length</b>	212.0 mm
<b>Width</b>	46.0 mm
<b>Height</b>	30.0 mm
<b>Mounting hole spacing, length</b>	202.0 mm
<b>Mounting hole spacing, width</b>	34.5 mm
<b>Cable cross-section, input side</b>	0.5...1.5 mm <sup>2</sup>
<b>Cable cross-section, output side</b>	0.5...1.5 mm <sup>2</sup>
<b>Product weight</b>	220.00 g
<b>Wire preparation length, input side</b>	5...6 mm
<b>Wire preparation length, output side</b>	5...6 mm
<b>Prewired</b>	No

Colors & materials

<b>Body material</b>	Plastic
----------------------	---------

Temperatures & operating conditions

<b>Ambient temperature range</b>	-10...+45 °C
<b>Maximum temperature at tc test point</b>	85 °C
<b>Max.housing temperature in case of fault</b>	95 °C
<b>Permitted rel. humidity during operation</b>	10...90 % <sup>1)</sup>

<sup>1)</sup> Maximum 56 days/year at 90%

Lifespan

<b>ECG lifetime</b>	35000 h <sup>1)</sup>
---------------------	-----------------------

<sup>1)</sup> At maximum T<sub>c</sub> = 85°C / 10% failure rate

Additional product data

<b>Encapsulated</b>	No
---------------------	----

## Capabilities

Dimmable	No
Overheating protection	No
Overload protection	Yes
Short-circuit protection	Yes
Max. cable length to lamp/LED module	2.0 m
Suitable for fixtures with prot. class	I / II
Type of connection, output side	Screw terminal
Suitable for no-load mode operation	Yes


## Certificates &amp; standards

Approval marks – approval	CE
Standards	Acc. to EN 61347-1/Acc. to EN 61347-2-13/Acc. to EN 55015/Acc. to EN 61547/Acc. to EN 61000-3-2/Acc. to EN 62384
Protection class	II
Type of protection	IP20

## Logistical data

Temperature range at storage	-20...+75 °C
------------------------------	--------------

## DOWNLOAD DATA

File
 User instruction LED DRIVER CONSTANT CURRENT VAL

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075240285	Shipping carton box 10	304 mm x 245 mm x 124 mm	2723.00 g	9.24 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## REFERENCES / LINKS

For Guarantee see

▶ [www.ledvance.com/guarantee](http://www.ledvance.com/guarantee)

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.