

# PRODUCT DATASHEET

## DULUX S LED EM 4.5 W/4000K

OSRAM DULUX S LED EM | LED replacement for short CFLni, with 2-pin G23 base for CCG and AC mains operation



---

### AREAS OF APPLICATION

- General illumination within ambient temperatures from -20...+45 °C
- Supermarkets and department stores
- Walkways and corridors
- Hotels, restaurants

---

### PRODUCT BENEFITS

- Quick, simple and safe replacement without rewiring
- Low energy consumption
- Easy relamping thanks to compact design

---

### PRODUCT FEATURES

- LED replacement for conventional compact fluorescent lamps for use in CCG luminaires or on AC mains
- Type of protection: IP20
- Lifetime: up to 30,000 h
- Single-ended two-pin plug-in G23 base



**TECHNICAL DATA**

Electrical data

<b>Rated wattage</b>	4.50 W
<b>Nominal wattage</b>	4.50 W
<b>Nominal voltage</b>	220...240 V
<b>Operating frequency</b>	50...60 Hz
<b>Power factor <math>\lambda</math></b>	> 0.50

Photometrical data

<b>Nominal luminous flux</b>	500 lm
<b>Rated luminous flux</b>	500 lm
<b>Rated color temperature</b>	4000 K
<b>Lumen main.fact.at end of nom.life time</b>	0.70
<b>Light color (designation)</b>	Cool White
<b>Color temperature</b>	4000 K
<b>Luminous flux</b>	500 lm
<b>Color rendering index Ra</b>	>80
<b>Standard deviation of color matching</b>	$\leq 6$ sdc <sub>m</sub>
<b>Color rendering index Ra</b>	>80

Light technical data

<b>Warm-up time (60 %)</b>	< 0.50 s
<b>Beam angle</b>	120 °
<b>Starting time</b>	< 0.5 s

Dimensions & weight



<b>Overall length</b>	166.0 mm
<b>Diameter</b>	33.0 mm
<b>Outer bulb</b>	-

<b>Length</b>	166.0 mm
---------------	----------

### Temperatures & operating conditions

<b>Ambient temperature range</b>	-20...+45 °C
<b>Maximum temperature at tc test point</b>	60 °C

### Lifespan

<b>Nominal lamp life time</b>	30000 h
<b>Rated lamp life time</b>	30000 h
<b>Number of switching cycles</b>	200000
<b>Lumen maintenance at end of service life</b>	0.70

### Additional product data

<b>Base (standard designation)</b>	G23
<b>Mercury content</b>	0.0 mg
<b>Mercury-free</b>	Yes
<b>Design / version</b>	Frosted
<b>Show WEEE picto</b>	Yes

### Capabilities

<b>Dimmable</b>	No
-----------------	----

### Certificates & standards

<b>Energy efficiency class</b>	A+
<b>Energy consumption</b>	5 kWh/1000h

### Country-specific categorizations

<b>Order reference</b>	DULUX S9LED 4,5
------------------------	-----------------

## SAFETY ADVICE

Not suitable for tandem operation.

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075135307	Folding carton box 1	24 mm x 36 mm x 175 mm	67.00 g	0.15 dm <sup>3</sup>
4058075135314	Shipping carton box 10	205 mm x 195 mm x 75 mm	573.00 g	3.00 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

**DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.